

Product data sheet  
Characteristics

81292

PratiKa industrijska vtičnica - 125 A - 3P + N + E - 200 do 250 V AC - IP67



Glavno

Skupina izdelkov	PratiKa
Izdelek ali sestavni del	Vtičnica
Kratko ime naprave	PratiKa vtičnica
Vtič, kategorija vtičnice	Nizka napetost
Opis polov	3P + N + E
Tip omrežja	AC
Standard vtičnice	Industrijski

Komplementarno

Montažni način	Ploščna montaža
Vtič, vtičnica, oblika krmilne postaje	Kotni
[In] nazivni tok	125 A
[Ue] Nazivna operativna napetost	200 do 250 V
Omrežna frekvenca	50/60 Hz
Ozemljitveni čas v smeri urinega kazalca	9 h
Vtič, material vtičnice	Ohišje Samougasljivi inženirni polimer
Material kontaktov	Zatiči Nerjaveče jeklo Obojka Medenina prevlečena z nikljem Vzmeti Nerjaveče jeklo
Povezave - terminali	Zarobljeni vijaki, popolnoma ohlapni
Presek kabla	16...70 Mm <sup>2</sup>
Teža izdelka	1,342 Kg
Osnovna dimenzija	110 x 114 mm
Višina	114 Mm
Širina	110 Mm
Globina	166 Mm
Barva	Siva (RAL 7035)
Barva napetosti	Modra

Okolje

Standardi	EN 60309-2 EN 60309-1
IP stopnja zaščite	IP67v skladu zIEC 60529
IK stopnja zaščite	IK08v skladu zEN 62262
Požarna odpornost	850 °C IEC 60695-2-11
Relativna vlažnost	50 % 40 °C 70 % 30 °C 90 % 20 °C
Temperatura okoliškega zraka za delovanje	35 °C 86400 s )

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Embalažna enota

Tip enote v embalaži 1	PCE
Število enot v embalaži 1	1
Teža embalaže 1	1,32 Kg
Višina embalaže 1	11,4 Cm
Širina embalaže 1	11,0 Cm
Dolžina embalaže 1	16,6 Cm
Tip enote v embalaži 2	S03
Število enot v embalaži 2	10
Teža embalaže 2	13,687 Kg
Višina embalaže 2	30,0 Cm
Širina embalaže 2	30,0 Cm
Dolžina embalaže 2	40,0 Cm

## Trajnost ponudbe

Status trajnostne ponudbe	Izdelek Green Premium
Uredba REACH	<a href="#">Izjava REACH</a>
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) <a href="#">Izjava EU RoHS</a>
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	<a href="#">Da</a>
Uredba o RoHS za Kitajsko	<a href="#">Izjava O RoHS Za Kitajsko</a>
Razkritje okoljskih podatkov	<a href="#">Okoljski Profil Izdelka</a>

## Pogodbena garancija

Garancija	18 months
-----------	-----------