

Product data sheet
Characteristics

81776

PratiKa industrijski vtič - 16 A - 3P + E - 100 do 130 V AC - IP67



Glavno

Skupina izdelkov	PratiKa
Izdelek ali sestavni del	Wander plug with phase inverter
Kratko ime naprave	PratiKa čep
Vtič, kategorija vtičnice	Nizka napetost
Opis polov	3P + E
Tip omrežja	AC
Standard vtičnice	Industrijski

Komplementarno

Vtič, vtičnica, oblika krmilne postaje	Kotni
[In] nazivni tok	16 A
[Ue] Nazivna operativna napetost	100 do 130 V
Omrežna frekvenca	50/60 Hz
Ozemljitveni čep v smeri urinega kazalca	4 h
Vtič, material vtičnice	Ohišje Samougasljivi inženirni polimer
Material kontaktov	Zatiči Medenina prevlečena z nikljem
Povezave - terminali	Zarobljeni vijaki
Presek kabla	1...4 Mm ²
Maksimalni zunanji premer kabla	8...15 Mm
Kabelska uvodnica	Kabelska uvodnica
Vrsta navoja	Pg 16
Teža izdelka	0,18 Kg
Višina	115 Mm
Širina	98 Mm
Globina	98 Mm
Barva	Siva (RAL 7035)
Barva napetosti	Rumena

Okolje

Standardi	IEC 60309-1 IEC 60309-2
IP stopnja zaščite	IP67v skladu zIEC 60529
IK stopnja zaščite	IK08v skladu zEN 62262
Požarna odpornost	850 °C IEC 60695-2-11
Relativna vlažnost	50 % 40 °C 70 % 30 °C 90 % 20 °C
Nadmorska višina delovanja	2000 m
Temperatura okoliškega zraka za delovanje	35 °C 86400 s) -25...40 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Embalažna enota

Teža embalaže 1	1,000 Kg
Višina embalaže 1	0,010 Dm
Širina embalaže 1	0,010 Dm
Dolžina embalaže 1	0,020 Dm