

Product data sheet
Characteristics

A9A15321

Acti 9 - iSO modularni zvonec 8 do 12 V AC -
80 dB - 3,6 VA



Predstavitev

Range of product	Acti 9
Ime izdelka	Acti 9 iSO
Izdelek ali sestavni del	Zvonec
Kratko ime naprave	ISO

Komplementarno

[Us] Nazivna napajalna napetost	8 do 12 V AC 50/60 Hz
Poraba energije v VA	3,6 VA
Montažni način	Pritrjen
Montažna podpora	35 mm simetrična DIN letev
9 mm rastri	2
Višina	81 Mm
Širina	18 Mm
Globina	72 Mm
Teža izdelka	77 G
Pomožni priključni terminal	Tunelski tip terminalov Togo 4 mm ² Tunelski tip terminalov Prilagodljiv 4 mm ² Tunelski tip terminalov Prilagodljivo s kapico 4 mm ²
Dolžina blankiranja žice	12 Mm Dno
Tightening torque	1,3 N.M Dno

Okolje

Stopnja hrupa	80 DB
Tip zvoka	Zvonec
IP stopnja zaščite	IP20IEC 60529 IP40 Modularna omara)IEC 60529
Temperatura okoliškega zraka za delovanje	-10...40 °C
Temperatura okoliškega zraka za skladiščenje	-25...60 °C

Trajnost ponudbe

Direktiva EU ROHS	Skladnost zagotovljena Izjava EU RoHS
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	Da
Uredba o RoHS za Kitajsko	Izjava O RoHS Za Kitajsko
OEE0	Na trgih Evropske unije je treba izdelek zavreči v skladu s posebnim postopkom zbiranja odpadkov in ga ni dovoljeno zavreči skupaj z gospodinjstskimi odpadki.

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.