



### Predstavitev

Range of product	Clario Acti 9 Librio ProDis
Izdelek ali sestavni del	Izpust podnapetosti
Kratko ime naprave	MNX
[Uc] Krmilna napetost	230 V AC 50/60 Hz
Tip krmiljenja	Z zunanjim napajanjem
9 mm rastri	2

### Komplementarno

Zdržljivost serije/obsega	Acti 9 iDPN Acti 9 C120 Acti 9 C40 Acti 9 C60H-DC Acti 9 C60NA-DC Acti 9 C60PV-DC Acti 9 DPN Vigi Acti 9 DT40 Acti 9 DT60 Acti 9 ID C40 Acti 9 IDc Acti 9 ITG40 Acti 9 ID Acti 9 DPN
Lokalno signaliziranje	Akcijski indikator
Montažni način	Pritrjen
Montažna podpora	35 mm simetrična DIN letev
Višina	82,5 Mm
Širina	18 Mm
Globina	73,5 Mm
Teža izdelka	73 G
Barva	Bela
Povezave - terminali	Vijačni priključek Dno) - 2 1,5 mm <sup>2</sup> - Prilagodljiv Vijačni priključek Dno) - 2 1,5 mm <sup>2</sup> - Prilagodljivo s kapico Vijačni priključek Dno) - 1 0,5...2,5 mm <sup>2</sup> - Togo
Dolžina blankiranja žice	9 Mm Dno
Tightening torque	1 N.M Dno
Kompatibilnostna koda	MNX

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Okolje

Standardi	EN/IEC 60947-5-1
Certifikati izdelkov	ASTA LCIE KEMA ASEFA
Tropikalizacija	2 EN/IEC 60947-5-1
Relativna vlažnost	95 % 55 °C
Temperatura okoliškega zraka za delovanje	-25...50 °C
Temperatura okoliškega zraka za skladiščenje	-40...85 °C

## Trajnost ponudbe

Status trajnostne ponudbe	Izdelek Green Premium
Uredba REACH	<a href="#">Izjava REACH</a>
Direktiva EU ROHS	Skladnost zagotovljena <a href="#">Izjava EU RoHS</a>
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	<a href="#">Da</a>
Uredba o RoHS za Kitajsko	<a href="#">Izjava O RoHS Za Kitajsko</a>
Razkritje okoljskih podatkov	<a href="#">Okoljski Profil Izdelka</a>
Profil krožnega gospodarstva	<a href="#">Informacije O Izteku Življenjske Dobe</a>
OEE0	Na trgih Evropske unije je treba izdelek zavreči v skladu s posebnim postopkom zbiranja odpadkov in ga ni dovoljeno zavreči skupaj z gospodinjskimi odpadki.

## Pogodbena garancija

Garancija	18 months
-----------	-----------