



Predstavitev

Skupina izdelkov	Acti 9
Ime izdelka	Acti 9 iSW
Izdelek ali sestavni del	Ločilno stikalo
Kratko ime naprave	ISW
Aplikacija naprave	Krmiljenje
Opis polov	1P
Kategorija uporabe	AC-22A
Primerno za izolativnost	Da

Komplementarno

Najvišji [I _e] nazivni obratovalni tok	32 A 250 V AC 50/60 Hz
[U _e] Nazivna operativna napetost	250 V AC 50/60 Hz
[U _i] Nazivna izolacijska trdnost	250 V AC 50/60 Hz EN/IEC 60669-2-4
[U _{imp}] Nazivna napetostna trdnost ob impulzu	4 KV
Tip krmiljenja	Preklop
Lokalno signaliziranje	Indikacija ON/OFF
Indikacija položaja kontakta	Da
Montažni način	Pritrjen
Montažna podpora	DIN letev
9 mm rastri	2
Višina	77 Mm
Širina	18 Mm
Globina	70 Mm
Barva	Siva
Mehanska vzdržljivost	300000 Cycles
Električna vzdržljivost	30000 Cycles
Povezave - terminali	Tunelski tip terminalov - 10 mm ² - Togo Tunelski tip terminalov - 10 mm ² - Prilagodljiv Tunelski tip terminalov - 10 mm ² - Prilagodljivo s kapico
Dolžina blankiranja žice	9 Mm
Zatezni moment	1,2 N.M

Okolje

Standardi	EN/IEC 60669-2-4
IP stopnja zaščite	IP4
Stopnja onesnaženosti	2
Tropikalizacija	2
Relativna vlažnost	95 % 55 °C
Temperatura okoliškega zraka za delovanje	-20...50 °C
Temperatura okoliškega zraka za skladiščenje	-40...70 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Embalažna enota

Teža embalaže 1	51,75 G
Teža embalaže 2	673,5 G
Teža embalaže 3	8,508 Kg

Trajnost ponudbe

Status trajnostne ponudbe	Izdelek Green Premium
Uredba REACH	Izjava REACH
REACH, brez snovi SVHC	Da
Direktiva EU ROHS	Skladnost zagotovljena Izjava EU RoHS
Brez strupenih težkih kovin	Da
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	Da
Uredba o RoHS za Kitajsko	Izjava O RoHS Za Kitajsko
Razkritje okoljskih podatkov	Okoljski Profil Izdelka
Profil krožnega gospodarstva	Informacije O Izteku Življenjske Dobe
OEE0	Na trgih Evropske unije je treba izdelek zavreči v skladu s posebnim postopkom zbiranja odpadkov in ga ni dovoljeno zavreči skupaj z gospodinjskimi odpadki.

Pogodbena garancija

Garancija	18 months
-----------	-----------