

## Product data sheet

### Characteristics

# BMXFCC303

Komplet kablov - 40-kanalni priključek - 2 x konektor HE10 - za M340 I/O - 3 m



#### Glavno

|                                    |  |
|------------------------------------|--|
| Serija izdelka                     | Modicon X80                              |
| Tip dodatkov/ločenih delov         | Predoblikovani kabli                     |
| Označevanje dodatkov/ločenih delov | Predoblikovani kabli za Telefast Adva    |
| Destinacija dodatkov/ločenih delov | Za I/O modul s 40-smernimi konektorji    |
| Število kablov                     | 2  |
| Električna povezava                | 1 konektor 40 smeri<br>2 konektorja HE10 |
| Dolžina kabla                      | 3 M                                      |

#### Komplementarno

|                    |                       |
|--------------------|-----------------------|
| Skupno število žic | 40                    |
| Žični odsek        | 0,324 Mm <sup>2</sup> |
| Teža izdelka       | 0,94 Kg               |

#### Embalážna enota

|                              |             |
|------------------------------|-------------|
| Unit Type of Package 1       | PCE         |
| Number of Units in Package 1 | 1           |
| Package 1 Height             | 5,500 Cm    |
| Package 1 Width              | 24,500 Cm   |
| Package 1 Length             | 24,500 Cm   |
| Package 1 Weight             | 886 G       |
| Unit Type of Package 2       | S02         |
| Number of Units in Package 2 | 6           |
| Package 2 Height             | 15,000 Cm   |
| Package 2 Width              | 30,000 Cm   |
| Package 2 Length             | 40,000 Cm   |
| Package 2 Weight             | 5,655 Kg    |
| Unit Type of Package 3       | P12         |
| Number of Units in Package 3 | 288         |
| Package 3 Height             | 101,000 Cm  |
| Package 3 Width              | 80,000 Cm   |
| Package 3 Length             | 120,000 Cm  |
| Package 3 Weight             | 2952,000 Kg |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Trajnost ponudbe

|                                |  |
|--------------------------------|--|
| Direktiva EU ROHS              | Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) <a href="#">Izjava EU RoHS</a> |
| Brez strupenih težkih kovin    | Da   |
| Brez živega srebra             | Da   |
| Informacije o izvzetju iz RoHS | <a href="#">Da</a>   |
| Uredba o RoHS za Kitajsko      | <a href="#">Izjava O RoHS Za Kitajsko</a>  |
| Razkritje okoljskih podatkov   | <a href="#">Okoljski Profil Izdelka</a>  |

## Pogodbena garancija

|           |           |
|-----------|-----------|
| Garancija | 18 months |
|-----------|-----------|