

Product data sheet

Characteristics

EZB250W12

Easypact zbiralka - 250 A - 12-kanalna



Glavno

Serijski izdelki	EasyPact
Skupina izdelkov	EasyPact
Kratko ime naprave	Zbiralka
Izdelek ali sestavni del	Zbiralka
Aplikacija naprave	Povezava
Združljivost serije/ obsega	EasyPact EZB Odklopnik
[In] nazivni tok	250 A
Število smeri	12 smeri

Komplementarno

[Ui] Nazivna izolacijska trdnost	690 V AC 50/60 Hz
[Ue] Nazivna operativna napetost	550 V AC 50/60 Hz
Število naprav	12 3P) 18 2P) 36 1P)
Razširitev zbiralke	Brez
[Icw] Dovoljen kratkotrajen nazivni tok	30 KA 1 s
Višina	568,5 Mm
Širina	416 Mm
Globina	82,5 Mm

Okolje

Standardi	IEC 60439
-----------	-----------

Embalažna enota

Teža embalaže 1	8,000 Kg
Višina embalaže 1	1,400 Dm
Širina embalaže 1	4,500 Dm
Dolžina embalaže 1	6,600 Dm

Trajnost ponudbe

Uredba REACH	Izjava REACH
REACH, brez snovi SVHC	Da
Direktiva EU ROHS	Skladnost zagotovljena Izjava EU RoHS
Brez strupenih težkih kovin	Da
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	Da
Uredba o RoHS za Kitajsko	Izjava O RoHS Za Kitajsko
OEE0	Na trgih Evropske unije je treba izdelek zavreči v skladu s posebnim postopkom zbiranja odpadkov in ga ni dovoljeno zavreči skupaj z gospodinjstvi odpadki.

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Pogodbena garancija

Garancija

18 months
