

## Product data sheet

### Characteristics

# MIP12112S

Mini nadometna omara Pragma - 1 x 12 modulov - zatemnjena vrata



### Glavno

Skupina izdelkov	Resi9
Ime izdelka	Resi9 MP
Izdelek ali sestavni del	Omara
Tip omare	Modularna omara
Nb of 18 mm modules per row	12
Nb of horizontal rows	1
Type of door	Dimljen
Širina	Zunaj 268 mm
Višina	Zunaj 228 mm
Globina	Zunaj 101,5 mm

### Komplementarno

Montaža omare	Nadometna
9 mm rastri	24
Skupno število 18 mm modulov	12
[In] Nazivni tok	63 A
Tip letve	35 mm asimetrična letev
Opis montažne plošče	Brez montažne plošče
Kabelska uvodnica	1 prirobnica 1 prirobnica kanala
Funkcionalnost vrstne sponke	Ozemljeni/Nevtraleni
Število terminalnih blokov	1 Ozemljitev Privit)8 1 Nevtralno Privit)8
Distribucijski bloki (izhodi)	1 x 16 mm <sup>2</sup> Ozemljitev 1 x 16 mm <sup>2</sup> Nevtralno 3 x 6 mm <sup>2</sup> Ozemljitev 3 x 6 mm <sup>2</sup> Nevtralno 4 x 10 mm <sup>2</sup> Ozemljitev 4 x 10 mm <sup>2</sup> Nevtralno
Material omare	Zadnji del Tehnoplastika Vrata Tehnoplastika Spredej Tehnoplastika
Notranja globina	80 Mm
Barva	Spredej Bela RAL 9003) Vrata Dimljen RAL 9003)
Tržni segment	Stanovanjska Majhno komercialno

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Okolje

Standardi	IEC 61439-1 IEC 61439-3 IEC 60670-1 IEC 60670-24
Oznake kakovosti	IMQ
Požarna odpornost	Vrata 650 °C Zadnji del 650 °C Spredaj 650 °C
IP stopnja zaščite	IP40
IK stopnja zaščite	IK07
Temperatura okoliškega zraka za delovanje	-25...60 °C

## Embalažna enota

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	10,400 Cm
Package 1 Width	23,100 Cm
Package 1 Length	27,500 Cm
Package 1 Weight	844,000 G
Unit Type of Package 2	CAR
Number of Units in Package 2	8
Package 2 Height	31,200 Cm
Package 2 Width	42,100 Cm
Package 2 Length	53,600 Cm
Package 2 Weight	7,016 Kg
Unit Type of Package 3	P12
Number of Units in Package 3	128
Package 3 Height	120,000 Cm
Package 3 Width	80,000 Cm
Package 3 Length	120,000 Cm
Package 3 Weight	124,256 Kg

## Trajnost ponudbe

Status trajnostne ponudbe	Izdelek Green Premium
Uredba REACH	<a href="#">Izjava REACH</a>
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) <a href="#">Izjava EU RoHS</a>
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	<a href="#">Da</a>
Uredba o RoHS za Kitajsko	<a href="#">Izjava O RoHS Za Kitajsko</a>
Razkritje okoljskih podatkov	<a href="#">Okoljski Profil Izdelka</a>
Vsebnost halogena	Izdelek brez halogena

## Pogodbena garancija

Garancija	18 months
-----------	-----------