

## Product data sheet

### Characteristics

# MIP22106

Mini podometna omara Pragma - 1 x 6 modulov - navadna vrata



### Glavno

|                             |  |
|-----------------------------|--|
| Skupina izdelkov            | Resi9                                    |
| Ime izdelka                 | Resi9 MP                                 |
| Izdelek ali sestavni del    | Omara                                    |
| Tip omare                   | Modularna omara                          |
| Nb of 18 mm modules per row | 6  |
| Nb of horizontal rows       | 1  |
| Type of door                | Navaden                                  |
| Širina                      | Zid 162 mm<br>Zunaj 186 mm               |
| Višina                      | Zid 228 mm<br>Zunaj 252 mm               |
| Globina                     | Zunaj 18 mm<br>Zid 80 mm<br>Skupaj 98 mm |

### Komplementarno

|                               |   |
|-------------------------------|---|
| Montaža omare                 | Podometna   |
| 9 mm rastri                   | 12  |
| Skupno število 18 mm modulov  | 6   |
| [In] Nazivni tok              | 63 A  |
| Tip letve                     | 35 mm asimetrična letev   |
| Opis montažne plošče          | Brez montažne plošče  |
| Kabelska uvodnica             | Prehodno rezane luknje  |
| Funkcionalnost vrstne sponke  | Ozemljeni/Nevtralen   |
| Število terminalnih blokov    | 1 Ozemljitev Privit)4<br>1 Nevtralno Privit)4   |
| Distribucijski bloki (izhodi) | 1 x 16 mm <sup>2</sup> Ozemljitev<br>1 x 16 mm <sup>2</sup> Nevtralno<br>1 x 6 mm <sup>2</sup> Ozemljitev<br>1 x 6 mm <sup>2</sup> Nevtralno<br>2 x 10 mm <sup>2</sup> Ozemljitev<br>2 x 10 mm <sup>2</sup> Nevtralno |
| Material omare                | Zadnji del Tehnoplastika<br>Vrata Tehnoplastika<br>Spreddaj Tehnoplastika   |
| Notranja globina              | 76 Mm   |
| Barva                         | Vrata Bela RAL 9003)<br>Spreddaj Bela RAL 9003)   |
| Tržni segment                 | Stanovanjska<br>Majhno komercialno  |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Okolje

|   |   |
|---|---|
| Standardi                                 | IEC 61439-1<br>IEC 61439-3<br>IEC 60670-1<br>IEC 60670-24 |
| Oznake kakovosti                          | IMQ   |
| Požarna odpornost                         | Vrata 650 °C<br>Zadnji del 650 °C<br>Spredaj 650 °C       |
| IP stopnja zaščite                        | IP40  |
| IK stopnja zaščite                        | IK07  |
| Temperatura okoliškega zraka za delovanje | -25...60 °C   |

## Embalažna enota

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 9,7 Cm    |
| Package 1 Width              | 18,6 Cm   |
| Package 1 Length             | 25,2 Cm   |
| Package 1 Weight             | 530,0 G   |
| Unit Type of Package 2       | BB1       |
| Number of Units in Package 2 | 12        |
| Package 2 Height             | 52,0 Cm   |
| Package 2 Width              | 30,0 Cm   |
| Package 2 Length             | 40,0 Cm   |
| Package 2 Weight             | 6,46 Kg   |
| Unit Type of Package 3       | P12       |
| Number of Units in Package 3 | 192       |
| Package 3 Height             | 120,0 Cm  |
| Package 3 Width              | 80,0 Cm   |
| Package 3 Length             | 120,0 Cm  |
| Package 3 Weight             | 115,36 Kg |

## Trajnost ponudbe

|                                |  |
|--------------------------------|--|
| Status trajnostne ponudbe      | Izdelek Green Premium  |
| Uredba REACH                   | <a href="#">Izjava REACH</a>   |
| Direktiva EU ROHS              | Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) <a href="#">Izjava EU RoHS</a> |
| Brez živega srebra             | Da   |
| Informacije o izvzetju iz RoHS | <a href="#">Da</a>   |
| Uredba o RoHS za Kitajsko      | <a href="#">Izjava O RoHS Za Kitajsko</a>  |
| Razkritje okoljskih podatkov   | <a href="#">Okoljski Profil Izdelka</a>  |
| Vsebnost halogena              | Izdelek brez halogena  |

## Pogodbena garancija

|           |           |
|-----------|-----------|
| Garancija | 18 months |
|-----------|-----------|