

## Product data sheet

### Characteristics

# NSYFPLS1827G

Poliestrski hrbtni del omare PLS 18 x 27 x 13,5 cm



#### Predstavitev

Skupina izdelkov	Thalassa
Ime izdelka	Thalassa PLS
Kratko ime naprave	PLS
Enclosure type	Večnamenski
Category	Izolacijski modularni zadnji
Nominal height	180 Mm
Nominal width	270 Mm
Nominal depth	135 Mm
Montaža omare	Stensko montirano
Sestava naprave	1 rear part: on enclosure
Tip ohišja	En kos oblikovan
Tip prednjega pokrova	Brez

#### Komplementarno

Material	Polyester reinforced with fibreglass
Barva	Ohišje Siva RAL 7035)
Standardi	Klasifikacija NEMA 13 IEC 62208 NEMA 4X
Certifikati izdelkov	UL

#### Okolje

Razred električne izolacije	Razred II
IP stopnja zaščite	IP66 IEC 60529
IK stopnja zaščite	IK09 conforming to IEC 62262
Požarna odpornost	960 °C conforming to IEC 62208
Temperatura okoliškega zraka za skladiščenje	-30...70 °C

#### Embalažna enota

Teža embalaže 1	0,890 Kg
-----------------	----------

#### Trajnost ponudbe

Uredba REACH	<a href="#">Izjava REACH</a>
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) <a href="#">Izjava EU RoHS</a>
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	<a href="#">Da</a>
Uredba o RoHS za Kitajsko	<a href="#">Izjava O RoHS Za Kitajsko</a>
Razkritje okoljskih podatkov	<a href="#">Okoljski Profil Izdelka</a>

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.