Product data sheet
Characteristics

PKX32M415
Gnezdni vtič PratiKa - raven - 32 A - 3P + N + E - 100 do 130 V AC - IP44

Glavno

Skupina izdelkov	PratiKa
Izdelek ali sestavni del	Wander plug
Kratko ime naprave	PratiKa čep
Vtič, kategorija vtičnice	Nizka napetost
Opis polov	3P + N + E
Tip omrežja	AC
Standard vtičnice	Industrijski

Komplementarno

Vtič, vtičnica, oblika krmilne postaje	Raven
[In] nazivni tok	32 A
[Ue] Nazivna operativna napetost	100 do 130 V
Omrežna frekvenca	50/60 Hz
Ozemljitveni čep v smeri urinega kazalca	4 h
Vtič, material vtičnice	Ohišje Samougasljivi inženirni polimer
Material kontaktov	Obojka Medenina
Povezave - terminali	Hitra povezava
Presek kabla	2,5…6 Mm²
Maksimalni zunanji premer kabla	11,5…21 Mm
Kabelska uvodnica	Kabelska uvodnica Fair lead
Vrsta navoja	Pg 21
Teža izdelka	0,278 Kg
Višina	160 Mm
Širina	86 Mm
Globina	86 Mm
Barva	Siva (RAL 7035)
Barva napetosti	Rumena

Okolje

Standardi	IEC 60309-1 IEC 60309-2
IP stopnja zaščite	IP44v skladu zIEC 60529
IK stopnja zaščite	IK08v skladu zEN 62262
Požarna odpornost	850 °C IEC 60695-2-11
Relativna vlažnost	50 % 40 °C 70 % 30 °C 90 % 20 °C
Nadmorska višina delovanja	2000 m
Temperatura okoliškega zraka za delovanje	35 °C 86400 s) −25…40 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Embalažna enota

Tip enote v embalaži 1	PCE
Število enot v embalaži 1	1
Teža embalaže 1	230,0 G
Višina embalaže 1	7,0 Cm
Širina embalaže 1	9,0 Cm
Dolžina embalaže 1	10,0 Cm

Trajnost ponudbe

Status trajnostne ponudbe	Izdelek Green Premium
Uredba REACH	Izjava REACh
Direktiva EU ROHS	Skladnost zagotovljena Izjava EU RoHS
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	Da
Uredba o RoHS za Kitajsko	Izjava O RoHS Za Kitajsko
Razkritje okoljskih podatkov	Okoljski Profil Izdelka
OEEO	Na trgih Evropske unije je treba izdelek zavreči v skladu s posebnim postopkom zbiranja odpadkov in ga ni dovoljeno zavreči skupaj z gospodinjskimi odpadki.

Pogodbena garancija

Garancija	18 months