

Product data sheet
Characteristics

PKY16G445
Vtičnica PratiKa - hitri priklj. - ravna - 16 A - 3P
+ N + E - 480 do 500 V AC



Glavno

| | |
|---------------------------|------------------|
| Skupina izdelkov | PratiKa |
| Izdelek ali sestavni del | Vtičnica |
| Kratko ime naprave | PratiKa vtičnica |
| Vtič, kategorija vtičnice | Nizka napetost |
| Opis polov | 3P + N + E |
| Tip omrežja | AC |
| Standard vtičnice | Industrijski |

Komplementarno

| | |
|--|--|
| Montažni način | Ploščna montaža |
| Vtič, vtičnica, oblika krmilne postaje | Raven |
| [In] nazivni tok | 16 A |
| [Ue] Nazivna operativna napetost | 480 do 500 V |
| Omrežna frekvenca | 50/60 Hz |
| Ozemljitveni čas v smeri urinega kazalca | 7 h |
| Vtič, material vtičnice | Ohišje Samougasljivi inženirni polimer |
| Material kontaktov | Obojka Medenina |
| Povezave - terminali | Hitra povezava |
| Presek kabla | 1...4 Mm ² |
| Teža izdelka | 0,208 Kg |
| Osnovna dimenzija | 90 x 100 mm |
| Višina | 100 Mm |
| Širina | 90 Mm |
| Globina | 94 Mm |
| Barva | Siva (RAL 7035) |
| Barva napetosti | Črna |

Okolje

| | |
|---|--|
| Standardi | IEC 60309-1 IEC 60309-2 |
| IP stopnja zaščite | IP44v skladu zIEC 60529 |
| IK stopnja zaščite | IK08v skladu zEN 62262 |
| Požarna odpornost | 850 °C IEC 60695-2-1 |
| Relativna vlažnost | 50 % 40 °C 70 % 30 °C 90 % 20 °C |
| Temperatura okoliškega zraka za delovanje | 35 °C 86400 s) |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Embalažna enota

| | |
|---------------------------|----------|
| Tip enote v embalaži 1 | PCE |
| Število enot v embalaži 1 | 1 |
| Teža embalaže 1 | 170,0 G |
| Višina embalaže 1 | 10,0 Cm |
| Širina embalaže 1 | 9,0 Cm |
| Dolžina embalaže 1 | 7,0 Cm |
| Tip enote v embalaži 2 | BB1 |
| Število enot v embalaži 2 | 10 |
| Teža embalaže 2 | 1,73 Kg |
| Višina embalaže 2 | 17,0 Cm |
| Širina embalaže 2 | 27,0 Cm |
| Dolžina embalaže 2 | 26,3 Cm |
| Tip enote v embalaži 3 | S03 |
| Število enot v embalaži 3 | 20 |
| Teža embalaže 3 | 3,947 Kg |
| Višina embalaže 3 | 30,0 Cm |
| Širina embalaže 3 | 30,0 Cm |
| Dolžina embalaže 3 | 40,0 Cm |

Pogodbena garancija

| | |
|-----------|-----------|
| Garancija | 18 months |
|-----------|-----------|