SINTEL

Product data sheet
Characteristics

PKY16G723
Vtičnica PratiKa - hitri priklj. - ravna - 16 A - 2P + E - 200 do 250 V AC

Glavno

Skupina izdelkov	PratiKa
Izdelek ali sestavni del	Vtičnica
Kratko ime naprave	PratiKa vtičnica
Vtič, kategorija vtičnice	Nizka napetost
Opis polov	2P + E
Tip omrežja	AC
Standard vtičnice	Industrijski

Komplementarno

Montažni način	Ploščna montaža
Vtič, vtičnica, oblika krmilne postaje	Raven
[In] nazivni tok	16 A
[Ue] Nazivna operativna napetost	200 do 250 V
Omrežna frekvenca	50/60 Hz
Ozemljitveni čep v smeri urinega kazalca	6 h
Vtič, material vtičnice	Ohišje Samougasljivi inženirni polimer
Material kontaktov	Obojka Medenina
Povezave - terminali	Hitra povezava
Presek kabla	1…2,5 Mm²
Teža izdelka	0,179 Kg
Osnovna dimenzija	65 x 85 mm
Barva	Siva (RAL 7035)
Barva napetosti	Modra

Okolje

Standardi	IEC 60309-1 IEC 60309-2
IP stopnja zaščite	IP67v skladu zIEC 60529
IK stopnja zaščite	IK08v skladu zEN 62262
Požarna odpornost	850 °C IEC 60695-2-1
Relativna vlažnost	50 % 40 °C 70 % 30 °C 90 % 20 °C
Temperatura okoliškega zraka za delovanje	35 °C 86400 s)

Embalažna enota

Tip enote v embalaži 1	PCE
Število enot v embalaži 1	1
Teža embalaže 1	141,0 G
Višina embalaže 1	7,1 Cm
Širina embalaže 1	8,9 Cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Dolžina embalaže 1	9,5 Cm
Tip enote v embalaži 2	BB1
Število enot v embalaži 2	10
Teža embalaže 2	1,577 Kg
Višina embalaže 2	12,0 Cm
Širina embalaže 2	27,0 Cm
Dolžina embalaže 2	26,3 Cm
Tip enote v embalaži 3	S03
Število enot v embalaži 3	30
Teža embalaže 3	5,218 Kg
Višina embalaže 3	30,0 Cm
Širina embalaže 3	30,0 Cm
Dolžina embalaže 3	40,0 Cm

Trajnost ponudbe

Status trajnostne ponudbe	Izdelek Green Premium
Uredba REACH	Izjava REACh
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) Izjava EU RoHS
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	Da
Uredba o RoHS za Kitajsko	Izjava O RoHS Za Kitajsko
Razkritje okoljskih podatkov	Okoljski Profil Izdelka

Pogodbena garancija

Garancija	18 months