

Product data sheet

Characteristics

PRA20224

Površinska omara Pragma - IP30 - 2 x 24 modulov - brez vrat



Glavno

| | |
|-----------------------------|---|
| Skupina izdelkov | Pragma |
| Izdelek ali sestavni del | Omara |
| Tip omare | Distribuirana omara |
| Širina | Zunaj 550 mm |
| Višina | 450 Mm |
| Globina | 148 Mm |
| Nb of 18 mm modules per row | 24 |
| Nb of horizontal rows | 2 |
| Razred električne izolacije | Dvojna izolativnost Razred II |
| Dobavljena oprema | 2 x Priključni blok 1 x Identifikacijska oznaka 1 x Označevalni komplet 1 x Blanking plate strip |
| Type of door | Brez |

Komplementarno

| | |
|----------------------------------|---|
| Montaža omare | Nadometna |
| 9 mm rastri | 48 |
| Skupno število 18 mm modulov | 48 |
| Maksimalne izgube v W | 67 W |
| [In] Nazivni tok | 125 A |
| [Ui] Nazivna izolacijska trdnost | 400 V |
| Tip letve | Multifix |
| Opis montažne plošče | Brez montažne plošče |
| Kabelska uvodnica | Kabel ali cev Izrezane plošče Kanali Odstranljive plošče |
| Število terminalnih blokov | 1 Ozemljitev Quick)27 1 Nevtralno Quick)29 |
| Distribucijski bloki (izhodi) | 2 x 25 mm ² Ozemljitev 24 x 6 mm ² Ozemljitev 1 x 50 mm ² Ozemljitev 1 x 50 mm ² Nevtralno 24 x 6 mm ² Nevtralno 4 x 25 mm ² Nevtralno |
| Material omare | Zadnji del Tehnoplastika Spredej Tehnoplastika Zadnji del Kovinski Spredej Kovinski |
| Barva | Omara Bela RAL 9016) Spredej Siva RAL 7004) |
| Tržni segment | Majhno komercialno Stanovanjska |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|------------------|---|
| Ciljna država | Švedska Finska Baltik Madžarska Republika Češka Grčija Rusija |
| Globina vgradnje | 0 Mm |
| Notranja globina | 120 Mm |

Okolje

| | |
|---|---|
| Požarna odpornost | Zadnji del 650 °C Spredej 650 °C |
| IP stopnja zaščite | IP30 Brez vrat IP40 Z vrati |
| IK stopnja zaščite | IK08 Brez vrat IK09 Z vrati |
| Prenapetostna kategorija | II |
| Temperatura okoliškega zraka za delovanje | -25...60 °C |
| Standardi | IEC 60670-1 IEC 60670-24 IEC 61439-1 IEC 61439-3 |

Embalažna enota

| | |
|------------------------------|------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 15,5 Cm |
| Package 1 Width | 54,0 Cm |
| Package 1 Length | 64,0 Cm |
| Package 1 Weight | 7,631 Kg |
| Unit Type of Package 2 | P12 |
| Number of Units in Package 2 | 18 |
| Package 2 Height | 120,0 Cm |
| Package 2 Width | 80,0 Cm |
| Package 2 Length | 120,0 Cm |
| Package 2 Weight | 149,358 Kg |

Trajnost ponudbe

| | |
|--------------------------------|--|
| Status trajnostne ponudbe | Izdelek Green Premium |
| Uredba REACH | Izjava REACH |
| REACH, brez snovi SVHC | Da |
| Direktiva EU ROHS | Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) Izjava EU RoHS |
| Brez strupenih težkih kovin | Da |
| Brez živega srebra | Da |
| Informacije o izvzetju iz RoHS | Da |
| Uredba o RoHS za Kitajsko | Izjava O RoHS Za Kitajsko |
| Razkritje okoljskih podatkov | Okoljski Profil Izdelka |
| Vsebnost halogena | Izdelek brez halogena |

Pogodbena garancija

| | |
|-----------|-----------|
| Garancija | 18 months |
|-----------|-----------|