

# PRA25313

Podometna omara Pragma - IP40 - 3 x 13  
modulov - brez vrat



## Glavno

Skupina izdelkov	Pragma
Izdelek ali sestavni del	Omara
Tip omare	Distribuirana omara
Širina	Zid 366 mm Zunaj 396 mm
Višina	Zid 630 mm Zunaj 660 mm
Globina	Zid 86 mm Zunaj 21 mm
Nb of 18 mm modules per row	13
Nb of horizontal rows	3
Razred električne izolacije	Razred II Dvojna izolativnost
Dobavljena oprema	2 x Priključni blok 1 x Identifikacijska oznaka 1 x Označevalni komplet 1 x Blanking plate strip
Type of door	Brez

## Komplementarno

Montaža omare	Podometna
9 mm rastri	26
Skupno število 18 mm modulov	39
Maksimalne izgube v W	56 W
[In] Nazivni tok	90 A
[Ui] Nazivna izolacijska trdnost	400 V
Tip letve	DIN
Opis montažne plošče	Brez montažne plošče
Kabelska uvodnica	Stranski pred-rezi Kabel ali cev Odstranljive plošče
Število terminalnih blokov	1 Ozemljitev Quick)24 1 Nevtralno Quick)24
Distribucijski bloki (izhodi)	3 x 25 mm <sup>2</sup> Ozemljitev 21 x 4 mm <sup>2</sup> Ozemljitev 3 x 25 mm <sup>2</sup> Nevtralno 21 x 4 mm <sup>2</sup> Nevtralno
Material omare	Zadnji del Tehnoplastika Spredej Tehnoplastika
Barva	Omara Bela RAL 9016) Spredej Siva RAL 7004)
Ciljna država	Madžarska Rusija Grčija Republika Češka
Globina vgradnje	86 Mm
Notranja globina	84 Mm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Okolje

Požarna odpornost	Zadnji del 650 °C Spredej 650 °C
IP stopnja zaščite	IP30 Brez vrat IP40 Z vrati
IK stopnja zaščite	IK08 Brez vrat IK09 Z vrati
Prenapetostna kategorija	II
Temperatura okoliškega zraka za delovanje	-25...60 °C
Standardi	IEC 60670-1 IEC 60670-24 IEC 61439-1 IEC 61439-3

## Embalážna enota

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	12,0 Cm
Package 1 Width	41,5 Cm
Package 1 Length	66,5 Cm
Package 1 Weight	4,431 Kg
Unit Type of Package 2	P12
Number of Units in Package 2	21
Package 2 Height	120,0 Cm
Package 2 Width	80,0 Cm
Package 2 Length	120,0 Cm
Package 2 Weight	105,051 Kg

## Trajnost ponudbe

Status trajnostne ponudbe	Izdelek Green Premium
Uredba REACH	 <a href="#">Izjava REACH</a>
REACH, brez snovi SVHC	Da
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS)  <a href="#">Izjava EU RoHS</a>
Brez strupenih težkih kovin	Da
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	 <a href="#">Da</a>
Uredba o RoHS za Kitajsko	 <a href="#">Izjava O RoHS Za Kitajsko</a>
Razkritje okoljskih podatkov	 <a href="#">Okoljski Profil Izdelka</a>
Vsebnost halogena	Izdelek brez halogena

## Pogodbena garancija

Garancija	18 months
-----------	-----------