

PRA25524

Podometna omara Pragma - IP40 - 5 x 24
modulov - brez vrat



Glavno

Skupina izdelkov	Pragma
Izdelek ali sestavni del	Omara
Tip omare	Distribuirana omara
Širina	Zid 570 mm Zunaj 610 mm
Višina	Zid 930 mm Zunaj 960 mm
Globina	Zunaj 30 mm Zid 95 mm
Nb of 18 mm modules per row	24
Nb of horizontal rows	5
Razred električne izolacije	Razred II Dvojna izolativnost
Dobavljena oprema	2 x Priključni blok 1 x Identifikacijska oznaka 1 x Označevalni komplet 1 x Blanking plate strip
Type of door	Brez

Komplementarno

Montaža omare	Podometna
9 mm rastri	48
Skupno število 18 mm modulov	120
Maksimalne izgube v W	133 W
[In] Nazivni tok	160 A
[Ui] Nazivna izolacijska trdnost	400 V
Tip letve	Multifix
Opis montažne plošče	Brez montažne plošče
Kabelska uvodnica	Kabel ali cev Odstranljive plošče Stranski pred-rezi
Število terminalnih blokov	1 Ozemljitev Quick)32 1 Nevtralno Quick)35
Distribucijski bloki (izhodi)	1 x 50 mm ² Ozemljitev 3 x 25 mm ² Ozemljitev 28 x 6 mm ² Ozemljitev 1 x 50 mm ² Nevtralno 28 x 6 mm ² Nevtralno 6 x 25 mm ² Nevtralno
Material omare	Zadnji del Tehnoplastika Spredaj Tehnoplastika Zadnji del Kovinski Spredaj Kovinski
Barva	Omara Bela RAL 9016) Spredaj Siva RAL 7004)
Tržni segment	Stanovanjska Majhno komercialno

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ciljna država	Rusija Grčija Madžarska Republika Češka
Globina vgradnje	95 Mm
Notranja globina	93 Mm



Okolje

Požarna odpornost	Zadnji del 650 °C Spredej 650 °C
IP stopnja zaščite	IP30 Brez vrat IP40 Z vrati
IK stopnja zaščite	IK08 Brez vrat IK09 Z vrati
Prenapetostna kategorija	II
Temperatura okoliškega zraka za delovanje	-25...60 °C
Standardi	IEC 60670-1 IEC 60670-24 IEC 61439-1 IEC 61439-3

Embalažna enota

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	15,5 Cm
Package 1 Width	65,0 Cm
Package 1 Length	99,0 Cm
Package 1 Weight	17,9 Kg
Unit Type of Package 2	P12
Number of Units in Package 2	9
Package 2 Height	120,0 Cm
Package 2 Width	80,0 Cm
Package 2 Length	120,0 Cm
Package 2 Weight	173,1 Kg

Trajnost ponudbe

Status trajnostne ponudbe	Izdelek Green Premium
Uredba REACH	 Izjava REACH
REACH, brez snovi SVHC	Da
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS)  Izjava EU RoHS
Brez strupenih težkih kovin	Da
Brez živega srebra	Da
Informacije o izvetju iz RoHS	 Da
Uredba o RoHS za Kitajsko	 Izjava O RoHS Za Kitajsko
Razkritje okoljskih podatkov	 Okoljski Profil Izdelka
Vsebnost halogena	Izdelek brez halogena

Pogodbena garancija

Garancija	18 months
-----------	-----------