Product data sheet
Characteristics

TA16D4S1604TPE
Preklopno stikalo, TransferPacT Automatic, 160A, 4P, vrtljiva stikala, ohišje 160A

Glavno

Serija izdelka	TransferPacT
Izdelek ali sestavni del	Automatic transfer switch
Aplikacija naprave	Spremenjen vir napajanja
Opis polov	4P
Tip omrežja	AC
Omrežna frekvenca	50/60 Hz
Povezava navzdol	Screwed
Montažni način	Pritrjen
Povezava navzgor	Screwed
Indikacija položaja kontakta	Da
[Icm] Nazivni kratkostični priklopni tok	154 KA Z zaščitnim odklopnikom v smeri proti toku 400 V AC pri50 Hz 20 KA Samo odklopnik s stikalom 400 V AC pri50 Hz
Primerno za izolativnost	Da

Komplementarno

Transfer switch class	PC
Število kontaktnih položajev	3
Sestava signalnih kontaktov	1 NO + 2 NC 1 NC + 2 NO 2 NO
Utilization category	AC-33B
[Ue] Nazivna operativna napetost	400 V AC 50/60 Hz
Tip krmiljenja	Vrtljiv gumb Izbirno stikalo
Način delovanja	Avtomatski Priročnik
Montažna podpora	Plošča DIN letev
Opis možnosti za zaklepanje	Ključavnica v položaju OFF
Nazivno delovanje	Neprekinjeno
[Ui] Nazivna izolacijska trdnost	Stikalo: 800 V Controller: 500 V
[Uimp] Nazivna napetostna trdnost ob impulzu	Stikalo: 8 kV Controller: 6 kV
Najvišji [Ie] nazivni obratovalni tok	160 A
Mehansko zapiranje	Z
Mehanska vzdržljivost	10000 Ciklov
Priključni raster	30 Mm
[Icw] Dovoljen kratkotrajen nazivni tok	10 KA med0.1 s
Višina	164 Mm
Širina	351 Mm
Globina	95 Mm
Teža izdelka	5,6 Kg
[Ith] Konvencionalni prostozračni toplotni tok	160 A pri60 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Okolje

Standardi	IEC 60947-6-1
Certifikati izdelkov	CE[RETURN]CB[RETURN]CCC
IP stopnja zaščite	Spredaj IP40 auto mode V omari IP20 manual mode
Temperatura okoliškega zraka za delovanje	−25…70 °C
Temperatura okoliškega zraka za skladiščenje	−35…85 °C
Stopnja onesnaženosti	3

Embalažna enota

Embalažna enota Paketa 1	PCE
Število enot v Paketu 1	1
Paket 1 Višina	14,000 Cm
Paket 1 Širina	22,500 Cm
Paket 1 Dolžina	40,000 Cm
Paket 1 Teža	6,550 Kg

Trajnost ponudbe

Status trajnostne ponudbe	Izdelek Green Premium
Uredba REACH	Izjava REACh
REACh, brez snovi SVHC	Da
Direktiva EU ROHS	Skladno z izjemami
Brez živega srebra	Da
Uredba o RoHS za Kitajsko	Izjava O RoHS Za Kitajsko
Informacije o izvzetju iz RoHS	Da
Razkritje okoljskih podatkov	Okoljski Profil Izdelka
Profil krožnega gospodarstva	Informacije O Izteku Življenjske Dobe