



Glavno

Ponudba	TeSys
Ime izdelka	TeSys VARIO
Kratko ime naprave	VBD
Aplikacija naprave	Preventivno vzdrževanje
Tip izdelka	Ločilno stikalo

Komplementarno

Sestava naprave	Stikalo Ročica
Mounting Support	Ročica Vrata Stikalo Vrata
Mounting Method	Luknja 22,5 mm Ročica
Performance Level	Visoka zmogljivost
Opis polov	3P
Tip in sestava kontaktov	3 NO
[Ue] IEC Rated Operational Voltage	690 V AC 50/60 Hz
IEC Rated Operational Power in W	11 KW 690 V AC-23A) 3 KW 230 do 240 V AC-3) 4 KW 400 do 415 V AC-3) 5,5 KW 500 V AC-3) 7,5 KW 500 V AC-23A) 7,5 KW 690 V AC-3) 4 KW 230 do 240 V AC-23A) 5,5 KW 400 do 415 V AC-23A)
[Ie] Rated Operational Current	11 A AC-23 Ue: 400 V
[Ith] Conventional Free Air Thermal Current	20 A
[Ithe] Conventional Enclosed Thermal Current	16 A
Making Capacity (I Rms)	200 A 400 V AC-21A 200 A 400 V AC-22A 200 A 400 V AC-23A
Breaking Capacity	200 A 400 V AC-21A) 200 A 400 V AC-22A) 200 A 400 V AC-23A)
Rated Conditional Short Circuit Current	10 KA 400 V 20 A aM 10 KA 400 V 20 A gG
[Icm] Rated Short Circuit Making Capacity	1 KA 400 V Pri lpeak
[Icw] Rated Short Time Withstand Current	300 A 400 V 1 s
[Uimp] Rated Impulse Withstand Voltage	8 KV
Suitability for Isolation	Da
Tip omrežja	DC AC
Prekinitveni razred obratovanja	30
Tip nadzora	Vrtljivja ročica
Rotary Handle Mounting Style	Neposredna

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Handle Color	Črna
Handle Front Plate Color	Črna
Rotary Handle Padlocking	1 do 3 ključavnice 4...8 mm
Označevanje	0 - 1
Mehanska vzdržljivost	100000 Ciklov
Electrical Durability	100000 Ciklov AC-21 30000 Ciklov DC-1 do 5
IEC Terminal Connection	Močnostni tokokrog Vijačni priključki 10 mm ² Trden Močnostni tokokrog Vijačni priključki 6 mm ² Prilagodljiv - S kabelskim koncem
Tightening Torque	Močnostni tokokrog 2,1 N.m Vijačni priključki
Base Dimension	60 x 60 mm
Višina	74 Mm
Širina	60 Mm
Teža izdelka	0,215 Kg

Okolje

Standardi	IEC 60947-3
Certifikati izdelka	CCC CSA GL UL UKCA
Stopnja zaščite	IP20v skladu zIEC 60529 IP65
Protective Treatment	TC
Mechanical Robustness	Vibracije 10 do 150 Hz 1 gn) IEC 60068-2-6 Šoki 11 ms 30 Gn) IEC 60068-2-27
Temperatura zraka v okolici za delovanje	-20...50 °C
Fire Resistance	960 °C IEC 60695-2-1
Kompatibilnostna koda	Glavno ločilno stikalo

Embalažna enota

Tip enote v embalaži 1	PCE
Število enot v embalaži 1	1
Teža embalaže 1	226 G
Višina embalaže 1	8 Cm
Širina embalaže 1	8 Cm
Dolžina embalaže 1	11,5 Cm
Tip enote v embalaži 2	S03
Število enot v embalaži 2	24
Teža embalaže 2	5,845 Kg
Višina embalaže 2	30 Cm
Širina embalaže 2	30 Cm
Dolžina embalaže 2	40 Cm

Trajnost ponudbe

Status trajnostne ponudbe	Izdelek Green Premium
Uredba REACH	Izjava REACH
REACH, brez snovi SVHC	Da
Direktiva EU ROHS	Skladnost zagotovljena Izjava EU RoHS
Brez strupenih težkih kovin	Da
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	Da
Uredba o RoHS za Kitajsko	Izjava O RoHS Za Kitajsko
Razkritje okoljskih podatkov	Okoljski Profil Izdelka

OEEO	Na trgih Evropske unije je treba izdelek zavreči v skladu s posebnim postopkom zbiranja odpadkov in ga ni dovoljeno zavreči skupaj z gospodinjskimi odpadki.
Brez PVC	Da
Vsebnost halogena	Izdelek brez halogena

Pogodbena garancija

Garancija	18 months
-----------	-----------