



Predstavitev

Serija izdelka	Altivar
Izdelek ali sestavni del	Vmesniška kartica enkoderja
Združljivost skupine izdelkov	Altivar 71 Altivar 71Q Altivar Lift
Tip enkoderja	SinCos Hiperface EnDat 2.2 SSI
[Us] Nazivna napajalna napetost	5 V 5...5,5 V) 8 V 8...8,5 V) 12 V 12...12,5 V)

Komplementarno

Združljivost izdelkov	ATV71H do M3383 ATV71H do M3X383 ATV71H do N4383
Maksimalni tok napajanja	0,2 A
Tip zaščite	Zaščita kratkega stika Zaščita pred preobremenitvijo
Maksimalna kabelna razdalja med napravami	50 M
Hitrost povratne resolucije	2exp(13) maksimum
Urna frekvenca	500 kHz Pritrjen
Tip izhoda	SinCos največ 10000 linij EnDat 2.1 maksimum 25 bitov SSI Grayev ali binarni brez, z liho ali sodo pariteto, nastavljiv SinCos Hiperface največ 10000 linij
Električna povezava	Terminal 0,5 mm ² AWG 20) <25 m, Enkoder, 100 mA 4,75 V Terminal 0,5 mm ² AWG 20) <25 m, Enkoder, 100 mA 7,75 V Terminal 0,5 mm ² AWG 20) <25 m, Enkoder, 100 mA 14,75 V Terminal 0,75 mm ² AWG 18) <50 m, Enkoder, 100 mA 4,75 V Terminal 0,75 mm ² AWG 18) <50 m, Enkoder, 100 mA 7,75 V Terminal 0,75 mm ² AWG 18) <50 m, Enkoder, 100 mA 14,75 V Terminal 1 mm ² AWG 17) <25 m, Enkoder, 200 mA 4,75 V Terminal 1 mm ² AWG 17) <25 m, Enkoder, 200 mA 7,75 V Terminal 1 mm ² AWG 17) <25 m, Enkoder, 200 mA 14,75 V Terminal 1,5 mm ² AWG 15) <50 m, Enkoder, 200 mA 4,75 V Terminal 1,5 mm ² AWG 15) <50 m, Enkoder, 200 mA 7,75 V Terminal 1,5 mm ² AWG 15) <50 m, Enkoder, 200 mA 14,75 V
Teža izdelka	0,2 Kg

Embalazna enota

Tip enote v embalaži 1	PCE
Število enot v embalaži 1	1
Teža embalaže 1	173 G
Višina embalaže 1	7,2 Cm
Širina embalaže 1	17,5 Cm
Dolžina embalaže 1	23,5 Cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Trajnost ponudbe

Uredba REACH	Izjava REACH
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) Izjava EU RoHS
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	Da
Uredba o RoHS za Kitajsko	Izjava O RoHS Za Kitajsko

Pogodbena garancija

Garancija	18 months
-----------	-----------