

Product data sheet

Characteristics

VW3A3420

Modul vmesnika digitalnega kodirnika 5/12 V



Predstavitev

Serijska izdelka	Altivar
Izdelek ali sestavni del	Vmesni modul digitalnega enkoderja
Združljivost skupine izdelkov	Altivar Process ATV900 Altivar Process Modular Altivar Machine ATV340
Protokol komunikacijskih vrat	RS422
Tip enkoderja	EnDat 2.2 A/B/I Inkrementalni XCC1 Tip R A/B/I Inkrementalni XCC1 Tip X SSI absolutni enkoder XCC2 Tip SG SSI absolutni enkoder XCC3 Tip SB
[Us] Nazivna napajalna napetost	5 V DC 4,75...5,25 V) 12 V DC 11,4...12,6 V) 24 V DC 22,8...25,2 V)

Komplementarno

Maksimalni tok napajanja	0,25 A 5 V DC 0,1 A 12 V DC 0,05 A 24 V DC
Tip zaščite	Zaščita kratkega stika Zaščita pred preobremenitvijo
Maksimalna kabelna razdalja med napravami	100 M A/B/I) 50 M SSI) 100 M SSI)Pri 300 kHz 50 M EnDat 2.2) 100 M EnDat 2.2)S kompenzacijo zakasnitve
Maksimalna delovna frekvenca	1000 kHz
Vhodni signal	Data+, Data- EnDat 2.2) Data+, Data- SSI) Temp +, Temp- A+,A-/B+,B-/I+,I- A/B/I) TTL
Vhodna impedanca	121 Ohm
Izhodni signal	Clock+, Clock- SSI) Data+, Data-, Clock+, Clock- EnDat 2.2)
Tip konektorja	1 Ženski SUB-D 15 visoke gostote
Teža izdelka	0,15 Kg

Embalazna enota

Teža embalaže 1	0,150 Kg
Višina embalaže 1	0,700 Dm
Širina embalaže 1	1,300 Dm
Dolžina embalaže 1	1,900 Dm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Trajnost ponudbe

Uredba REACH	Izjava REACH
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) Izjava EU RoHS
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	Da
Uredba o RoHS za Kitajsko	Izjava O RoHS Za Kitajsko
Brez PVC	Da