

## Product data sheet

### Characteristics

# VW3A3422

## Modul vmesnika analognega kodirnika



### Predstavitev

Serija izdelka	Altivar
Izdelek ali sestavni del	Analogni enkoderski vmesniški modul
Združljivost skupine izdelkov	Altivar Machine ATV340 Altivar Process ATV900 Altivar Process Modular
Tip enkoderja	SinCos Hiperface 1 Vpp
[Us] Nazivna napajalna napetost	5 V DC 4,75...5,25 V) 12 V DC 11,4...12,6 V) 24 V DC 22,8...25,2 V)

### Komplementarno

Maksimalni tok napajanja	0,25 A 5 V DC 0,1 A 12 V DC 0,05 A 24 V DC
Tip zaščite	Zaščita pred preobremenitvijo Zaščita kratkega stika
Maksimalna kabelna razdalja med napravami	100 M
Maksimalna delovna frekvenca	100 kHz
Vhodni signal	Data+, Data-, Sin, RefSin, Cos, RefCos, Temp+, Temp-
Izhodni signal	Data+, Data-
Tip konektorja	1 Ženski SUB-D 15 visoke gostote
Teža izdelka	0,15 Kg

### Embalažna enota

Teža embalaže 1	0,151 Kg
Višina embalaže 1	0,660 Dm
Širina embalaže 1	1,300 Dm
Dolžina embalaže 1	1,900 Dm

### Trajnost ponudbe

Uredba REACH	<a href="#">Izjava REACH</a>
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) <a href="#">Izjava EU RoHS</a>
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	<a href="#">Da</a>
Uredba o RoHS za Kitajsko	<a href="#">Izjava O RoHS Za Kitajsko</a>
Brez PVC	Da

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.