

Product data sheet

Characteristics

VW3A4402

Dodaten EMC vtisni filter S3 - 3-fazno napajanje - 26 A



Predstavitev

Serijska izdelka	Altivar
Izdelek ali sestavni del	EMC vhodni filter
Združljivost skupine izdelkov	Altivar 61 Altivar 71
Združljivost izdelkov	ATV61HU22M3 ATV61HU30M3 ATV61HU30N4 ATV61HU40M3 ATV61HU40N4 ATV71HU22M3 ATV71HU30M3 ATV71HU30N4 ATV71HU40M3 ATV71HU40N4 ATV71PU30N4Z ATV71PU40N4Z ATV71WU30N4 ATV71WU40N4
Uporaba izdelka za specifične aplikacije	Radijski interferenčni vhodni filter
Največji [In] nazivni tok	26 A
Toplotne izgube	18 W 200 do 240 V AC ATV61/ATV71 pogon s spremenljivo hitrostjo 6 W 380 do 480 V AC ATV61/ATV71 pogoni s spremenljivo hitrostjo
Število faz omrežja	Trifazni

Komplementarno

Električna povezava	Terminal 6 mm ² AWG 8
Zatezni moment	1,5 N.M
Maximum earth leakage current	8 MA 400 V 50 Hz 4,4 MA 400 V 50 Hz
Power supply voltage	200...240 V 380...500 V
Toleranca	10 %
Teža izdelka	4 Kg

Okolje

IP stopnja zaščite	IP20 IP41 (Zgornji del)
Relativna vlažnost	0...93 % IEC 68-2-3
Temperatura okoliškega zraka za delovanje	-10...50 °C
Temperatura okoliškega zraka za skladiščenje	-40...65 °C
Nadmorska višina delovanja	1000...3000 m S tokovno redukcijo 1% na 100 m
Odpornost proti vibracijam	1 gn 13...150 Hz)IEC 60068-2-6 1,5 mm od vrha do vrha 3...13 Hz)IEC 60068-2-6
Odporno proti udarcu	15 gn 11 ms EN/IEC 60068-2-27
Standardi	EN 133200 EN/IEC 61800-3

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Embalažna enota

Teža embalaže 1	4,965 Kg
Višina embalaže 1	1,300 Dm
Širina embalaže 1	5,900 Dm
Dolžina embalaže 1	2,550 Dm

Trajnost ponudbe

Uredba REACH	Izjava REACH
REACH, brez snovi SVHC	Da
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) Izjava EU RoHS
Brez strupenih težkih kovin	Da
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	Da
Uredba o RoHS za Kitajsko	Izjava O RoHS Za Kitajsko

Pogodbena garancija

Garancija	18 months
-----------	-----------