

Product data sheet

Characteristics

VW3A4424

Dodatni EMC filter - 47 A - 3 PH



Predstavitev

| | |
|--|--|
| Serijska izdelka | Altivar Lexium |
| Izdelek ali sestavni del | EMC vhodni filter |
| Združljivost skupine izdelkov | Altivar Machine ATV320 Lexium 28 Altivar 32 Lexium 32 |
| Združljivost izdelkov | LXM28A ATV32, 380 do 500 V, 5 do 7,5 kW LXM32M, Tri-fazni, linijski tok 19,9 do 23,3 A Pogon s spremenljivo hitrostjo ATV320 5,5 kW, 380 do 500 V, Trifazni Pogon s spremenljivo hitrostjo ATV320 7,5 kW, 380 do 500 V, Trifazni Variable speed drive ATV320...W/ATV320...WS at 5.5 kW, 380...500 V, three phase Variable speed drive ATV320...W/ATV320...WS at 7.5 kW, 380...500 V, three phase |
| Uporaba izdelka za specifične aplikacije | Radijski interferenčni vhodni filter |
| Lokacija montaže | Pod pogonom s spremenljivo hitrostjo |
| Število faz omrežja | Trifazni |

Komplementarno

| | |
|---|--|
| Maksimalna kabelna razdalja med napravami | 20 M IEC 61800-3 kategorija C1 50 M IEC 61800-3 kategorija C2 |
| Največji [In] nazivni tok | 47 A |
| Toplotne izgube | 19,3 W |
| Nazivna napetost omrežja | 380...500 V |
| Toleranca | - 15 do 10 % |
| Teža izdelka | 3,15 Kg |
| Združljivost z emc filtrom | Tip 024 |

Embalazna enota

| | |
|---------------------------|----------|
| Tip enote v embalaži 1 | PCE |
| Število enot v embalaži 1 | 1 |
| Teža embalaže 1 | 3,01 Kg |
| Višina embalaže 1 | 7 Cm |
| Širina embalaže 1 | 46,8 Cm |
| Dolžina embalaže 1 | 24 Cm |
| Tip enote v embalaži 2 | S06 |
| Število enot v embalaži 2 | 22 |
| Teža embalaže 2 | 80,76 Kg |
| Višina embalaže 2 | 73,5 Cm |
| Širina embalaže 2 | 60 Cm |
| Dolžina embalaže 2 | 80 Cm |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Trajnost ponudbe

| | |
|--------------------------------|--|
| Uredba REACH | Izjava REACH |
| REACH, brez snovi SVHC | Da |
| Direktiva EU ROHS | Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) Izjava EU RoHS |
| Brez strupenih težkih kovin | Da |
| Brez živega srebra | Da |
| Informacije o izvzetju iz RoHS | Da |
| Uredba o RoHS za Kitajsko | Izjava O RoHS Za Kitajsko |

Pogodbena garancija

| | |
|-----------|-----------|
| Garancija | 18 months |
|-----------|-----------|