

## Product data sheet

### Characteristics

# VW3A4521

DC dušilka - 0,21 mH - 243 A - za pogon s spremenljivo hitrostjo



#### Predstavitev

Izdelek ali sestavni del	DC dušenje
Aplikacija naprave	Reduciranje tokovnih harmonikov
Vrednost induktivnosti	0,21 MH
Največji [In] nazivni tok	243 A

#### Komplementarno

Maksimalni tok	1,65 x nominalni tok 60 s)
----------------	----------------------------

#### Embalažna enota

Teža embalaže 1	25,000 Kg
Višina embalaže 1	2,900 Dm
Širina embalaže 1	3,300 Dm
Dolžina embalaže 1	3,800 Dm

#### Trajnost ponudbe

Uredba REACH	<a href="#">Izjava REACH</a>
REACH, brez snovi SVHC	Da
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) <a href="#">Izjava EU RoHS</a>
Brez strupenih težkih kovin	Da
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	<a href="#">Da</a>
Uredba o RoHS za Kitajsko	<a href="#">Izjava O RoHS Za Kitajsko</a>

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.