



### Predstavitev

Izdelek ali sestavni del	LR filterska celica
Združljivost skupine izdelkov	Altivar 31C Altivar 312 Easy Altivar 310 Altivar 312 Solar Easy Altivar 310L
Uporaba izdelka za specifične aplikacije	Izhodni filter
Združljivost izdelkov	ATV312H018M2 ATV312H018M3 ATV312H037M2 ATV312H037M3 ATV312H037N4 ATV312H055M2 ATV312H055M3 ATV312H055N4 ATV312H075M2 ATV312H075M3 ATV312H075N4 ATV312H075S6 ATV312HU11M2 ATV312HU11M3 ATV312HU11N4 ATV312HU15M2 ATV312HU15M3 ATV312HU15N4 ATV312HU22N4 ATV312HU22S6 ATV312HU30N4 ATV312HU40N4 ATV312HU40S6 ATV312HU55S6 ATV31C018M2 ATV31C037M2 ATV31C037N4 ATV31C055M2 ATV31C055N4 ATV31C075M2 ATV31C075N4 ATV31CD11N4 ATV31CD15N4 ATV31CU11M2 ATV31CU11N4 ATV31CU15M2 ATV31CU15N4 ATV31CU22N4 ATV31CU30N4 ATV31CU40N4 Pogon s spremenljivo hitrostjo ATV310 0,37 kW Pogon s spremenljivo hitrostjo ATV310 0,75 kW Pogon s spremenljivo hitrostjo ATV310 1,5 kW Pogon s spremenljivo hitrostjo ATV310L 0,75 kW Pogon s spremenljivo hitrostjo ATV310L 1,5 kW Pogon s spremenljivo hitrostjo ATV310L 2,2 kW Pogon s spremenljivo hitrostjo ATV310L 3,0 kW Pogon s spremenljivo hitrostjo ATV310L 4,0 kW Pogon s spremenljivo hitrostjo ATV310L 5,5 kW
Maximum length of motor cable	100 M Zaščiten kabel 0,5 do 4 kHz)
Toplotne izgube	150 W
Največji [In] nazivni tok	10 A

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Komplementarno

Teža izdelka	7,4 Kg
--------------	--------

## Okolje

IP stopnja zaščite	IP20
--------------------	------

## Embalažna enota

Tip enote v embalaži 1	PCE
Število enot v embalaži 1	1
Teža embalaže 1	7,217 Kg
Višina embalaže 1	22,5 Cm
Širina embalaže 1	26,5 Cm
Dolžina embalaže 1	51,6 Cm
Tip enote v embalaži 2	P06
Število enot v embalaži 2	6
Teža embalaže 2	56,3 Kg
Višina embalaže 2	80 Cm
Širina embalaže 2	80 Cm
Dolžina embalaže 2	60 Cm

## Trajnost ponudbe

Uredba REACH	<a href="#">Izjava REACH</a>
REACH, brez snovi SVHC	Da
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) <a href="#">Izjava EU RoHS</a>
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	<a href="#">Da</a>
Uredba o RoHS za Kitajsko	<a href="#">Izjava O RoHS Za Kitajsko</a>

## Pogodbena garancija

Garancija	18 months
-----------	-----------