

Product data sheet

Characteristics

VW3A7602R07

Zaviralni upornik - 27 Ohmov - 100 W - kabel
0,75 m - IP65



Predstavitev

Serijska izdelka	Lexium Altivar
Izdelek ali sestavni del	Zavorni upor
Združljivost skupine izdelkov	Lexium 28 Lexium 32i Lexium 52 Lexium 05 Lexium 32 Lexium 15 Easy Lexium 16
Združljivost izdelkov	Servo pogon LXM16D 0,75 kW, 200 do 230 V, Enofazni Servo pogon LXM16D 1 kW, 200 do 230 V, Enofazni Servo pogon LXM16D 1,5 kW, 200 do 230 V, Enofazni
Ohmska vrednost	27 Ohm
Neprekinjena moč	100 W
Dolžina kabla	0,75 M

Komplementarno

Vrh (maks.) energije	1900 J 400 V 3800 J 230 V 1900 J 480 V 4200 J 115 V
Tip zaščite	Toplotna zaščita preko servo pogona
Teža izdelka	0,63 Kg

Okolje

Temperatura okoliškega zraka za delovanje	0...50 °C
Temperatura okoliškega zraka za skladiščenje	-25...85 °C
IP stopnja zaščite	IP65
IP stopnja zaščite	IP65

Embalažna enota

Teža embalaže 1	0,630 Kg
Višina embalaže 1	0,450 Dm
Širina embalaže 1	4,000 Dm
Dolžina embalaže 1	1,300 Dm

Pogodbena garancija

Garancija	18 months
-----------	-----------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.