

**Product data sheet**  
Characteristics

**XAWF140EX**

Krmilna postaja - XAW-F - kovinska - 1 NO + 1 NC - črna - vklop-izklop



**Glavno**

Serija izdelka	Harmony XAW
Izdelek ali sestavni del	Kompletna krmilna postaja
Kratko ime naprave	XAWF
Aplikacija krmilne postaje	Funkcija start/stop
Material	Kovinski
Sestava krmilne postaje	1 izbirno stikalo s kličem, Črna, Stalni 1 NO + 1 NC

**Komplementarno**

Barva osnove omare	Črna
Barva pokrova	Črna
Kabelska uvodnica	1 vhod za ISO M20 kabelsko uvodnico
Širina	80 Mm
Globina	77 Mm
Višina	80 Mm
Teža izdelka	0,900 Kg
Označevanje	Ex tb IIIC T85°C Db IP65
Številka ključa	455
Mehanska vzdržljivost	1000000 Ciklov
Kratkostična zaščita	10 A Varovalka modula gG
[Ie] nazivni obratovalni tok	3 A 240 V, AC-15, A600 EN/IEC 60947-5-1 6 A 120 V, AC-15, A600 EN/IEC 60947-5-1 0,1 A 600 V, DC-13, Q600 EN/IEC 60947-5-1 0,27 A 250 V, DC-13, Q600 EN/IEC 60947-5-1 0,55 A 125 V, DC-13, Q600 EN/IEC 60947-5-1 1,2 A 600 V, AC-15, A600 EN/IEC 60947-5-1

**Okolje**

Temperatura okoliškega zraka za delovanje	-20...60 °C
Prenapetostna kategorija	I IEC 60536
IP stopnja zaščite	IP65 IEC 60529
Standardi	EN 60079-0:2009 EN 60079-31:2009 EN 60947-5-4 EN 61000-6-2 EN/IEC 60947-1 EN/IEC 60947-5-1 IEC 60079-0:2007 IEC 60079-31:2008
Direktive	94/9/EC - ATEX direktiva
Cona prahu	Cona 21 -22
Certifikati izdelkov	INERIS 04ATEX0023X

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Embalažna enota

Teža embalaže 1	0,620 Kg
Višina embalaže 1	0,770 Dm
Širina embalaže 1	0,800 Dm
Dolžina embalaže 1	0,800 Dm

## Pogodbena garancija

Garancija	18 months
-----------	-----------