

Product data sheet

Characteristics

XAWG310EX

Krmilna postaja - XAW-G - plastika - 1 NO - zelena - tri funkcije



Glavno

Serija izdelka	Harmony XAW
Izdelek ali sestavni del	Kompletna krmilna postaja
Kratko ime naprave	XAWG
Aplikacija krmilne postaje	Tri funkcije
Material	Okrepjeno s steklenimi vlakni
Sestava krmilne postaje	1 tipka, Zelena, Povratna vzmet 1 NO 1 tipka, Rdeča, Povratna vzmet 1 NC 1 tipka, Črna, Povratna vzmet 1 NO

Komplementarno

Barva osnove omare	Črna
Barva pokrova	Črna
Kabelska uvodnica	1 vhod za ISO M20 kabelsko uvodnico
Širina	85 Mm
Globina	70 Mm
Višina	226 Mm
Teža izdelka	0,915 Kg
Označevanje	Ex tb IIIC T85°C Db IP65
Mehanska vzdržljivost	5000000 Ciklov
Kratkostična zaščita	10 A Varovalka modula gG
[Ie] nazivni obratovalni tok	3 A 240 V, AC-15, A600 EN/IEC 60947-5-1 6 A 120 V, AC-15, A600 EN/IEC 60947-5-1 0,1 A 600 V, DC-13, Q600 EN/IEC 60947-5-1 0,27 A 250 V, DC-13, Q600 EN/IEC 60947-5-1 0,55 A 125 V, DC-13, Q600 EN/IEC 60947-5-1 1,2 A 600 V, AC-15, A600 EN/IEC 60947-5-1

Okolje

Temperatura okoliškega zraka za delovanje	-20...60 °C
Prenapetostna kategorija	II IEC 60536
IP stopnja zaščite	IP65 IEC 60529
Standardi	EN 60079-0:2009 EN 60079-31:2009 EN 60947-5-4 EN 61000-6-2 EN/IEC 60947-1 EN/IEC 60947-5-1 IEC 60079-0:2007 IEC 60079-31:2008 EN 60947-5-5 EN/ISO 13850
Direktive	94/9/EC - ATEX direktiva
Cona prahu	Cona 21 -22
Certifikati izdelkov	INERIS 04ATEX0023X

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Embalažna enota

Tip enote v embalaži 1	PCE
Število enot v embalaži 1	1
Teža embalaže 1	680 G
Višina embalaže 1	7 Cm
Širina embalaže 1	8,5 Cm
Dolžina embalaže 1	22,6 Cm
Tip enote v embalaži 2	CAR
Število enot v embalaži 2	1
Teža embalaže 2	680 G
Višina embalaže 2	22,9 Cm
Širina embalaže 2	12,5 Cm
Dolžina embalaže 2	8,6 Cm
Tip enote v embalaži 3	S02
Število enot v embalaži 3	4
Teža embalaže 3	4,455 Kg
Višina embalaže 3	15 Cm
Širina embalaže 3	30 Cm
Dolžina embalaže 3	40 Cm

Trajnost ponudbe

Uredba REACH	Izjava REACH
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) Izjava EU RoHS
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	Da
Uredba o RoHS za Kitajsko	Izjava O RoHS Za Kitajsko

Pogodbena garancija

Garancija	18 months
-----------	-----------