

XCMD21F2L2

Omejitveno stikalo XCMD - jekleni valjni bat
M12 - 1NC+1NO - proženje - 2 m



Glavno

Seriya izdelka	Telemecanique Limit switches XC Standard
Ime serije	Standardni format
Izdelek ali sestavni del	Mejno stikalo
Kratko ime naprave	XCMD
Zasnova senzorja	Miniaturni
Tip ohišja	Fiksen
Tip glave	M12 glava bata
Material	Kovinski
Material ohišja	Zamak
Material glave	Zamak
Način pritrjevanja	Ob glavi
Gibanje operativne glave	Linearno
Tip upravljanja	Spring return roller plunger metal
Tip pristopa	Lateral approach, 2 directions
Število polov	2
Tip kontakta in sestava	1 NC + 1 NO
Premik kontakta	Hitro ukrepanje

Komplementarno

Stikalno aktiviranje	S 30° odmikom
Električna povezava	Removable cable connector
Dolžina kabla	2 M
Sestava kablov	5 x 0,75 mm ²
Izolacijski material žiče	PvR
Kontaktna izolacijska oblika	ZB
Pozitivna odprtina	Z
Pozitivna minimalna sila	35 N
Minimalna sila za izklop	7 N
Maksimalna hitrost aktiviranja	10 Cm/S
Oznaka kontaktne kode	B300, AC-15 (U _e = 240 V), I _e = 1.5 A conforming to EN/IEC 60947-5-1 appendix A R300, DC-13 (U _e = 250 V), I _e = 0.1 A conforming to EN/IEC 60947-5-1 appendix A
[Ui] Nazivna izolacijska trdnost	300 V (pollution degree 3) conforming to UL 508 400 V (pollution degree 3) conforming to IEC 60947-5-1 300 V (pollution degree 3) conforming to CSA C22.2 No 14
Maksimalna odpornost na terminalih	25 MOhm conforming to IEC 60255-7 category 3
[Uimp] Nazivna napetostna trdnost ob impulzu	4 KV IEC 60664 4 KV IEC 60947-1
Kratkostična zaščita	6 A Modul Tailna varovalka gG
Električna vzdržljivost	5000000 Cycles, DC-13, 120 V, 1 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 Cycles, DC-13, 24 V, 3 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 Cycles, DC-13, 48 V, 2 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Mehanska vzdržljivost	10000000 Ciklov
Širina	30 Mm
Višina	50 Mm
Globina	16 Mm

Okolje

Odporno proti udarcu	25 gn 18 ms IEC 60068-2-27
Odpornost proti vibracijam	5 gn (f= 10...500 Hz) conforming to IEC 60068-2-6
IP stopnja zaščite	IP66 IEC 60529 IP67 IEC 60529 IP68 IEC 60529
IK stopnja zaščite	IK06 conforming to EN 62262
Prenapetostna kategorija	Razred I IEC 61140 Razred I NF C 20-030
Temperatura okoliškega zraka za delovanje	-25...70 °C
Temperatura okoliškega zraka za skladiščenje	-40...70 °C
Zaščitna obdelava	TC
Certifikati izdelkov	UL CSA CCC
Standardi	EN/IEC 60947-5-1 CSA C22.2 št. 14 UL 508 EN/IEC 60204-1

Packing Units

Teža embalaže 1	317,515 G
-----------------	-----------

Offer Sustainability

Status trajnostne ponudbe	Izdelek Green Premium
Uredba REACH	Izjava REACH
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) Izjava EU RoHS
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	Da
Razkritje okoljskih podatkov	Okoljski Profil Izdelka
Profil krožnega gospodarstva	Informacije O Izteku Življenjske Dobe

Pogodbena garancija

Garancija	18 months
-----------	-----------