

Product data sheet

Characteristics

XS9D111A1L2

Induktivni senzor XS9 80x80x26 - PBT - Sn 40 mm - 24 V DC - kabel 2 m



Predstavitev

Serija izdelka	OsiSense XS
Ime serije	Aplikacija
Tip sensorja	Induktivni senzor bližine
Aplikacija naprave	-
Ime sensorja	XS9
Zasnova sensorja	Ploščata oblika 80 x 80 x 26
Velikost	26 mm
Tip ohišja	Fiksen
Detector flush mounting acceptance	Podometno montirano
Material	Plastika
Material omare	PBT
Tip izhodnega signala	Analogni
Tehnika ožičenja	3-žična
[Sn] Nazivna razdalja zaznavanja	40 Mm
Izhodni tip tokokroga	DC
Območje analognega izhoda	0 do 10 V
Električna povezava	Kabel
Dolžina kabla	2 M
[Us] Nazivna napajalna napetost	24 V DC
IP stopnja zaščite	IP68 double insulation conforming to IEC 60529

Komplementarno

Detection face	Čelni
Prednji material	PBT
Operativna cona	5...40 Mm
Natančnost ponovitve	<= 3% od Sr
Napaka linearnosti	+/- 1 V
Sestava kablov	3 x 0,34 mm ²
Material izolacije žice	PvR
Status LED	Without
Omejitev napajalne napetosti	15...36 V DC
Preklopna frekvenca	<= 100 Hz
Poraba toka	0 do 4 mA Brez obremenitve
Maksimalni izhodni tokovni odvod	10 %
Označevanje	CE
Globina	26 Mm
Višina	80 Mm
Širina	80 Mm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.




Okolje

Certifikati izdelkov	UL Ecolab CSA
Temperatura okoliškega zraka za delovanje	-25...70 °C
Temperatura okoliškega zraka za skladiščenje	-40...85 °C
Odpornost proti vibracijam	25 gn +/- 2 mm 10...55 Hz)IEC 60068-2-6
Odporno proti udarcu	50 gn 11 ms IEC 60068-2-27

Embalažna enota

Teža embalaže 1	0,419 Kg
Višina embalaže 1	1,320 Dm
Širina embalaže 1	0,660 Dm
Dolžina embalaže 1	0,950 Dm

Trajnost ponudbe

Uredba REACH	 Izjava REACH
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS)  Izjava EU RoHS
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	 Da

Pogodbena garancija

Garancija	18 months
-----------	-----------