

## Product data sheet

### Characteristics

# XUFS0810

Opt. vl. za usm. svetlobe za ojačevalec - steklo  
- 0,97 m - zaznavna razd. 20 mm



#### Glavno

Serijska izdelka	Telemecanique Photoelectric sensors XU
Ime senzorja	XUF

#### Komplementarno

Tip elektronskega senzorja	Foto-električni senzor
Zasnova senzorja	Zasnova vlaken
Destinacija izdelka	XUDA
Sheath material	PE

#### Okolje

Odpornost proti vibracijam	+/- 1.5 mm (f= 10...55 Hz) conforming to IEC 60068-2-6 7 gn (f= 10...55 Hz) conforming to IEC 60068-2-6
Odporno proti udarcu	30 Gn 11 ms) IEC 60068-2-27
IP stopnja zaščite	IP64 IEC 60529 IP641 conforming to NF C 20-010

#### Packing Units

Tip enote v embalaži 1	PCE
Število enot v embalaži 1	1
Teža embalaže 1	42 G
Višina embalaže 1	3,4 Cm
Širina embalaže 1	6,2 Cm
Dolžina embalaže 1	13,5 Cm
Tip enote v embalaži 2	S02
Število enot v embalaži 2	44
Teža embalaže 2	2,277 Kg
Višina embalaže 2	15 Cm
Širina embalaže 2	30 Cm
Dolžina embalaže 2	40 Cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

Uredba REACH	<a href="#">Izjava REACH</a>
REACH, brez snovi SVHC	Da
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) <a href="#">Izjava EU RoHS</a>
Brez strupenih težkih kovin	Da
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	<a href="#">Da</a>