

Product data sheet

Characteristics

XVBL1G7

Ø 70 mm sign. semaf. - utripajoč - prosojen -
IP65 - 120 V



Glavno

Serijska izdelka	Harmony XVB Universal
Izdelek ali sestavni del	Kompletni žarek
Beacon or indicator bank unit type	Osnovna enota Neposredno ali cevno pritrjevanje Osvelitvena enota
Tip signalizacije	Utripajoče
Montažni premer	70 Mm
Ime komponente	XVBL
Material	S steklom okrepljeni poliamid: Osnovna enota Polikarbonat: Osvelitvena enota
Izvor svetlobe	Integrirana LED, Prozorna
Tip žarnice	Zaščitena LED
[Us] Nazivna napajalna napetost	120 V AC

Komplementarno

Povezave - terminali	Vijačni priključki, <= 1 x 1,5 mm ² S kabelskim koncem
[Ui] Nazivna izolacijska trdnost	250 V IEC 60947-1
Nazivno omejitev napetosti	0,85 do 1,1 Un IEC 60947-5-1
Poraba toka	< 17 mA AC
[Uimp] Nazivna napetostna trdnost ob impulzu	4 KV IEC 60947-1
Utripajoča frekvenca	1 Hz
CAD celotna širina	70 Mm
CAD celotna višina	139 Mm
CAD celotna globina	70 Mm
Opis sponke ISO št. 1	(GND)GROUND (COM-1)PW
Teža izdelka	0,28 Kg

Okolje

Stopnja onesnaženosti	2
Certifikati izdelkov	CSA C22-2 št. 14 GOST CCC UL 508
Standardi	EN/IEC 60947-5-1
Zaščitna obdelava	TC
Temperatura okoliškega zraka za skladiščenje	-40...70 °C
Razred električnega udara	Razred I Na nosilni cevi IEC 61140 Razred II Na osnovni enoti IEC 61140
IP stopnja zaščite	IP65 Na pritrditvenem podnožju XVBZ0. IEC 60529 IP66 Na osnovni enoti IEC 60529
Stopnja zaščite NEMA	NEMA 4X UL 508 Notranja)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Embalažna enota

Teža embalaže 1	0,287 Kg
Višina embalaže 1	1,450 Dm
Širina embalaže 1	0,800 Dm
Dolžina embalaže 1	0,800 Dm

Pogodbena garancija

Garancija	18 months
-----------	-----------