

Product data sheet

Characteristics

XVC1M2HK

100-mm sign. semaf. 100 do 240 V s sireno - stalna/utripajoča LED - oran./rdeča



Glavno

| | |
|--------------------------------|--|
| Serija izdelka | Harmony XVC1 |
| Izdelek ali sestavni del | Kompletni predožičeni monolitski signalni semafor |
| Tip signalnega svetilnika | 2 osvetlitveni enoti |
| Zvočno signaliziranje | Sirena |
| Montažni premer | 100 Mm |
| Ime komponente | XVC |
| Izvor svetlobe | LED Stalno ali utripajoče Rdeča LED Stalno ali utripajoče Oranžna |
| [Us] Nazivna napajalna npetost | 100 do 240 V |
| Tip napajalnega tokokroga | AC |
| Stopnja hrupa | 0...102 DB Neprekinjen ali prekinjen ton)1 m |

Komplementarno

| | |
|--|---|
| Material | Polikarbonat: Osvetlitvena enota ABS: Osnovna enota PBT + ABS (UL94-V0): Zgornji pokrov |
| Montaža izdelka | Na podnožju |
| Presek kabla | 0,33 Mm ² 0,83 Mm ² |
| Presek AWG | AWG 18 AWG 22 |
| Dolžina kabla | 500 Mm |
| Označevanje | CE |
| [Uimp] Nazivna napetostna trdnost ob impulzu | 4 KV |
| Poraba toka | 280 mA |
| Utripajoča frekvenca | 0,7...3 Hz |
| Teža izdelka | 1,88 Kg |
| Višina | 371 Mm |

Okolje

| | |
|--|------------------------------------|
| Standardi | EN/IEC 60947-5-1 EN/IEC 60947-1 |
| Certifikati izdelkov | UL |
| Zaščitna obdelava | TC |
| Temperatura okoliškega zraka za skladiščenje | -35...70 °C |
| Temperatura okoliškega zraka za delovanje | -20...50 °C |
| Razred električnega udara | Razred I EN/IEC 61140 |
| IP stopnja zaščite | IP54 EN/IEC 60529 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Embalažna enota

| | |
|---------------------------|---------|
| Tip enote v embalaži 1 | PCE |
| Število enot v embalaži 1 | 1 |
| Teža embalaže 1 | 2,74 Kg |
| Višina embalaže 1 | 18 Cm |
| Širina embalaže 1 | 18 Cm |
| Dolžina embalaže 1 | 63 Cm |

Pogodbena garancija

| | |
|-----------|-----------|
| Garancija | 18 months |
|-----------|-----------|