

Product data sheet

Characteristics

XVC1M3K

100-mm sign. semafor., vpet v ROG bazo, 100 do 240 V AC



Glavno

Serija izdelka	Harmony XVC1
Izdelek ali sestavni del	Kompletni predožičeni monolitski signalni semafor
Tip signalnega svetilnika	3 osvetlitvene enote
Zvočno signaliziranje	Brez
Montažni premer	100 Mm
Ime komponente	XVC
Izvor svetlobe	LED Stalno ali utripajoče Rdeča LED Stalno ali utripajoče Oranžna LED Stalno ali utripajoče Zelena
[Us] Nazivna napajalna npetost	100 do 240 V
Tip napajalnega tokokroga	AC

Komplementarno

Material	Polikarbonat: Osvetlitvena enota ABS: Osnovna enota PBT + ABS (UL94-V0): Zgornji pokrov
Montaža izdelka	Na podnožju
Presek kabla	0,33 Mm ² 0,83 Mm ²
Presek AWG	AWG 22 AWG 18
Dolžina kabla	500 Mm
Označevanje	CE
[Uimp] Nazivna napetostna trdnost ob impulzu	4 KV
Poraba toka	160 mA
Utripajoča frekvenca	0,7...3 Hz
Teža izdelka	1,4 Kg
Višina	372 Mm

Okolje

Standardi	EN/IEC 60947-5-1 EN/IEC 60947-1
Certifikati izdelkov	UL
Zaščitna obdelava	TC
Temperatura okoliškega zraka za skladiščenje	-35...70 °C
Temperatura okoliškega zraka za delovanje	-30...50 °C
Razred električnega udara	Razred I EN/IEC 61140
IP stopnja zaščite	IP54 EN/IEC 60529

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Embalažna enota

Tip enote v embalaži 1	PCE
Število enot v embalaži 1	1
Teža embalaže 1	1,995 Kg
Višina embalaže 1	22 Cm
Širina embalaže 1	22 Cm
Dolžina embalaže 1	45 Cm
Tip enote v embalaži 2	P06
Število enot v embalaži 2	6
Teža embalaže 2	24,97 Kg
Višina embalaže 2	80 Cm
Širina embalaže 2	80 Cm
Dolžina embalaže 2	60 Cm

Trajnost ponudbe

Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) Izjava EU RoHS
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	Da
Uredba o RoHS za Kitajsko	Izjava O RoHS Za Kitajsko
Razkritje okoljskih podatkov	Okoljski Profil Izdelka
Profil krožnega gospodarstva	Informacije O Izteku Življenjske Dobe

Pogodbena garancija

Garancija	18 months
-----------	-----------