

Product data sheet

Characteristics

XVC6B15SK

60-mm sign. semafor., podometno brenčalo
vpeto v R bazo



Glavno

Serija izdelka	Harmony XVC6
Izdelek ali sestavni del	Kompletni predožičeni monolitski signalni semafor
Tip signalnega svetilnika	1 osvetljena enota
Zvočno signaliziranje	Brenčač
Montažni premer	60 Mm
Ime komponente	XVC
Izvor svetlobe	LED Stalno ali utripajoče Rdeča
[Us] Nazivna napajalna npetost	24 V
Tip napajalnega tokokroga	AC/DC
Stopnja hrupa	70...85 DB Neprekinjen ali prekinjen ton)1 m

Komplementarno

Material	Polikarbonat: Osvetlitvena enota ABS: Osnovna enota PBT + ABS (UL94HB): Zgornji pokrov
Montaža izdelka	Na podnožju
Presek kabla	0,33 Mm ²
Presek AWG	AWG 22
Dolžina kabla	850 Mm
Označevanje	CE
[Uimp] Nazivna napetostna trdnost ob impulzu	0,8 KV
Poraba toka	65 mA
Temeljna frekvenca	2,23 KHz
Utripajoča frekvenca	1 Hz
Teža izdelka	0,2 Kg
Višina	120,8 Mm

Okolje

Standardi	EN/IEC 61000-6-2 EN/IEC 61000-6-4 EN/IEC 61000-6-3
Certifikati izdelkov	UL
Zaščitna obdelava	TC
Temperatura okoliškega zraka za skladiščenje	-35...70 °C
Temperatura okoliškega zraka za delovanje	-10...50 °C
Razred električnega udara	Razred II EN/IEC 61140
IP stopnja zaščite	IP54 Namestitvev na ravni površini EN/IEC 60529

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Embalažna enota

Tip enote v embalaži 1	PCE
Število enot v embalaži 1	1
Teža embalaže 1	430 G
Višina embalaže 1	8,8 Cm
Širina embalaže 1	9 Cm
Dolžina embalaže 1	50,5 Cm
Tip enote v embalaži 2	S04
Število enot v embalaži 2	12
Teža embalaže 2	6,42 Kg
Višina embalaže 2	30 Cm
Širina embalaže 2	40 Cm
Dolžina embalaže 2	60 Cm

Trajnost ponudbe

Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) Izjava EU RoHS
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	Da
Uredba o RoHS za Kitajsko	Izjava O RoHS Za Kitajsko
Razkritje okoljskih podatkov	Okoljski Profil Izdelka
Profil krožnega gospodarstva	Informacije O Izteku Življenjske Dobe

Pogodbena garancija

Garancija	18 months
-----------	-----------