SINTEL

Product data sheet
Characteristics

ZB4BH03
Zelena glava podometne tipke Ø 22 potisni-potisni, neoznačena

Glavno

Serija izdelka	Harmony XB4
Izdelek ali sestavni del	Glava za nesvetlečo tipko
Kratko ime naprave	ZB4
Material roba	Kromirana kovina
Montažni premer	22 Mm
Prodaja na nedeljivo količino	1
Tip glave	Standard
Oblika glave signalne enote	Okroglo
Tip upravljanja	Potisk-potisk
Profil operaterja	Zelena Podometna, Neoznačeni

Komplementarno

CAD celotna širina	29 Mm
CAD celotna višina	29 Mm
CAD celotna globina	28 Mm
Mehanska vzdržljivost	5000000 Ciklov
Koda električne sestave	C11 for <3 contacts using single blocks in front mounting C15 1 Enojni Prednja montaža C9 3 Enojni Prednja montaža
Predstavitev naprave	Osnovni element

Okolje

Zaščitna obdelava	TH
Temperatura okoliškega zraka za skladiščenje	−40…70 °C
Temperatura okoliškega zraka za delovanje	−40…70 °C
Prenapetostna kategorija	Razred I IEC 60536
IP stopnja zaščite	IP69 IP69K IP67 IEC 60529
Stopnja zaščite NEMA	NEMA 13 NEMA 4X
IK stopnja zaščite	IK06 conforming to IEC 50102
Standardi	UL 508 EN/IEC 60947-5-4 EN/IEC 60947-1 JIS C8201-5-1 EN/IEC 60947-5-5 CSA C22.2 št. 14 EN/IEC 60947-5-1 JIS C8201-1
Certifikati izdelkov	DNV LROS (Lloyds register pošiljke) CSA GL UL naveden BV

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof.
Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Odpornost proti vibracijam	5 gn 2…500 Hz)IEC 60068-2-6
Odporno proti udarcu	30 Gn 18 ms) Pospešek s sinusnim polvaljem IEC 60068-2-27 50 gn 11 ms) Pospešek s sinusnim polvaljem IEC 60068-2-27

Packing Units

Tip enote v embalaži 1	PCE
Število enot v embalaži 1	1
Teža embalaže 1	29 G
Višina embalaže 1	3,4 Cm
Širina embalaže 1	4,5 Cm
Dolžina embalaže 1	5,4 Cm
Tip enote v embalaži 2	BB1
Število enot v embalaži 2	5
Teža embalaže 2	145 G
Višina embalaže 2	3,4 Cm
Širina embalaže 2	4,5 Cm
Dolžina embalaže 2	26,5 Cm
Tip enote v embalaži 3	S03
Število enot v embalaži 3	300
Teža embalaže 3	9,413 Kg
Višina embalaže 3	30 Cm
Širina embalaže 3	30 Cm
Dolžina embalaže 3	40 Cm

Offer Sustainability

Status trajnostne ponudbe	Izdelek Green Premium
Uredba REACH	Izjava REACh
REACh, brez snovi SVHC	Da
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) Izjava EU RoHS
Brez strupenih težkih kovin	Da
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	Da
Uredba o RoHS za Kitajsko	Izjava O RoHS Za Kitajsko
Razkritje okoljskih podatkov	Okoljski Profil Izdelka
Profil krožnega gospodarstva	Informacije O Izteku Življenjske Dobe

Contractual warranty

Garancija	18 months