

Product data sheet

Characteristics

ZC1BD137

Kontaktni blok s tipko ZC1 - priključki z vijačnimi objemkami



Predstavitev

Serijska izdelka	Harmony XB4
Izdelek ali sestavni del	Kontaktni blok
Kratko ime naprave	ZC1
Prodaja na nedeljivo količino	1
Premik kontakta	Počasen izklop

Komplementarno

Povezave - terminali	Terminali vijačne sponke
Teža izdelka	0,05 Kg
Operating travel	4.3 Mm (total travel)
[Uimp] Nazivna napetostna trdnost ob impulzu	6 KV EN 60947-1
Najvišji [Ie] nazivni obratovalni tok	3 A at 240 V, AC-15, A600 conforming to EN/IEC 60947-5-1 6 A at 120 V, AC-15, A600 conforming to EN/IEC 60947-5-1 0.1 A at 600 V, DC-13, Q600 conforming to EN/IEC 60947-5-1 0.27 A at 250 V, DC-13, Q600 conforming to EN/IEC 60947-5-1 0.55 A at 125 V, DC-13, Q600 conforming to EN/IEC 60947-5-1 1.2 A at 600 V, AC-15, A600 conforming to EN/IEC 60947-5-1
Električna vzdržljivost	1000000 Cycles, AC-15, 2 A at 230 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C 1000000 Cycles, AC-15, 3 A at 120 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C 1000000 Cycles, AC-15, 4 A at 24 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C 1000000 Cycles, DC-13, 0.2 A at 110 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C 1000000 Cycles, DC-13, 0.5 A at 24 V, operating rate <3600 cyc/h, load factor: 0.5 conforming to EN/IEC 60947-5-1 appendix C
Električna izolativnost	$\Lambda < 10\exp(-7)$ 5 V, 1 mA V čistem okolju EN/IEC 60947-5-4 $\Lambda < 10\exp(-8)$ at 17 V, 5 mA in clean environment conforming to EN/IEC 60947-5-4

Okolje

Odporno proti udarcu	30 gn (duration = 18 ms) for half sine wave acceleration conforming to IEC 60068-2-27 50 gn (duration = 11 ms) for half sine wave acceleration conforming to IEC 60068-2-27
----------------------	--

Embalažna enota

Tip enote v embalaži 1	PCE
Število enot v embalaži 1	1
Teža embalaže 1	51 G
Višina embalaže 1	3 Cm
Širina embalaže 1	4,5 Cm
Dolžina embalaže 1	6 Cm