

Product data sheet

Characteristics

ZC2JE056

Glava omejitvenega stikala ZC2J - brez vzvoda za levi ali desni vklop - -40 °C



Glavno

Serijska izdelka	OsiSense XC
Ime serije	Posebni format
Izdelek ali sestavni del	Glava mejnega stikala
Kratko ime naprave	ZC2J
Tip glave	Vrtljiva glava
Združljivost izdelkov	XC2J
Povezana ročica	ZC2JY51 ZC2JY13 ZC2JY91 ZC2JY81 ZC2JY12 ZC2JY11 ZC2JY31
Povezano ohišje	ZC2JD26 ZC2JD16 ZC2JC16 ZC2JC26
Gibanje operativne glave	Vrtljiv
Tip upravljanja	Brez krmilne ročice Povratna vzmet
Tip pristopa	Bočni pristop, 1 Programljiv a smer

Komplementarno

Stikalno aktiviranje	CW ali CCW Od leve ali desne
Pozitivna odprtina	Brez
Teža izdelka	0,21 Kg
Material glave	Kovinski

Okolje

Temperatura okoliškega zraka za delovanje	-40...70 °C
Temperatura okoliškega zraka za skladiščenje	-40...70 °C
Okoljske značilnosti	Nizka temperatura

Packing Units

Tip enote v embalaži 1	PCE
Število enot v embalaži 1	1
Teža embalaže 1	210 G
Višina embalaže 1	4,2 Cm
Širina embalaže 1	4,2 Cm
Dolžina embalaže 1	9,1 Cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Status trajnostne ponudbe	Izdelek Green Premium
Uredba REACH	Izjava REACH
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) Izjava EU RoHS
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	Da
Razkritje okoljskih podatkov	Okoljski Profil Izdelka

Pogodbena garancija

Garancija	18 months
-----------	-----------