

Product data sheet

Characteristics

ZC2JE62

Glava omejitvenega stikala ZC2J - jekleni valjni bat



Glavno

Serijski izdelki	OsiSense XC
Ime serije	Posebni format
Izdelek ali sestavni del	Glava mejnega stikala
Kratko ime naprave	ZC2J
Tip glave	Glava bata
Združljivost izdelkov	XC2J
Povezani ohišja	ZC2JD1 ZC2JC1 ZC2JC28 ZC2JD2 ZC2JC2 ZC2JC18
Gibanje operativne glave	Linearno
Tip upravljanja	Valjasti bat Povratna vzmet Kovinski
Tip pristopa	Bočni pristop, 2 smeri

Komplementarno

Stikalno aktiviranje	S 30° odmikom
Pozitivna odprtina	Brez
Teža izdelka	0,2 Kg
Material glave	Kovinski

Okolje

Temperatura okoliškega zraka za delovanje	-25...70 °C
Temperatura okoliškega zraka za skladiščenje	-40...70 °C
Okoljske značilnosti	Standard

Packing Units

Tip enote v embalaži 1	PCE
Število enot v embalaži 1	1
Teža embalaže 1	214 G
Višina embalaže 1	5 Cm
Širina embalaže 1	9,4 Cm
Dolžina embalaže 1	4,8 Cm
Tip enote v embalaži 2	S01
Število enot v embalaži 2	14
Teža embalaže 2	3,193 Kg
Višina embalaže 2	15 Cm
Širina embalaže 2	15 Cm
Dolžina embalaže 2	40 Cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Status trajnostne ponudbe	Izdelek Green Premium
Uredba REACH	Izjava REACH
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) Izjava EU RoHS
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	Da
Razkritje okoljskih podatkov	Okoljski Profil Izdelka

Pogodbena garancija

Garancija	18 months
-----------	-----------