

Product data sheet

Characteristics

ZC2JY513

Vzvod omej. stik. ZC2JY - 3-mm kvadr. palica iz nerj. jekla - korozivni



Glavno

Serija izdelka	OsiSense XC
Ime serije	Posebni format
Izdelek ali sestavni del	Vzvod/Ročica mejnega stikala
Kratko ime naprave	ZC2J
Združljivost izdelkov	XC2J
Povezana glava	ZC2JE07 ZC2JE01 ZC2JE05 ZC2JE02 ZC2JE06 ZC2JE03 ZC2JE04
Gibanje operativne glave	Vrtljiv
Tip upravljanja	Vzvodna palica Povratna vzmet Kovinski Kvadratna palica 3 mm, L = 125 mm)
Tip pristopa	Bočni pristop

Komplementarno

Stikalno aktiviranje	S katerim koli gibljivim delom
Pozitivna odprtina	Brez

Okolje

Temperatura okoliškega zraka za delovanje	-25...70 °C Standard -40...70 °C Nizka temperatura 10...120 °C Visoka temperatura
Temperatura okoliškega zraka za skladiščenje	-40...70 °C Standard -40...70 °C Nizka temperatura 10...120 °C Visoka temperatura
Okoljske značilnosti	Nizka temperatura Visoka temperatura Korozivni

Packing Units

Tip enote v embalaži 1	PCE
Število enot v embalaži 1	1
Teža embalaže 1	35 G
Višina embalaže 1	2 Cm
Širina embalaže 1	3 Cm
Dolžina embalaže 1	12,5 Cm

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Status trajnostne ponudbe	Izdelek Green Premium
Uredba REACH	Izjava REACH
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) Izjava EU RoHS
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	Da
Razkritje okoljskih podatkov	Okoljski Profil Izdelka

Pogodbena garancija

Garancija	18 months
-----------	-----------