

ZCD21

Ohišje omejitvenega stikala ZCD - kompaktno -
1NC+1NO - hitro proženje



Glavno

Serijski izdelki	Telemecanique Limit switches XC Standard
Ime serije	Standardni kompaktni
Izdelek ali sestavni del	Ohišje mejnega stikala
Kratko ime naprave	ZCD
Zasnova	Compact
Tip ohišja	Fiksen
Povezana glava	ZCE66 ZCEH0 ZCE08 ZCE21 ZCE14 ZCE13 ZCE24 ZCE07 ZCE02 ZCE29 ZCE01 ZCE63 ZCE06 ZCE28 ZCE27 ZCE64 ZCE09 ZCE65 ZCE62 ZCE11 ZCEH2 ZCE10 ZCE05 ZCE67
Material ohišja	Zamak
Število polov	2
Tip kontakta in sestava	1 NC + 1 NO
Premik kontakta	Hitro ukrepanje

Komplementarno

Povezana komponenta povezave	ZCDEG13 ZCDEF12 ZCDEN12 ZCDEP20 ZCDEP16 ZCDEG11
Električna povezava	Terminali z vijakno objemko 1 x 0,34 do 2 x 1,5 mm ²
Kontaktna izolacijska oblika	ZB
Material kontaktov	Posrebreni kontakti
Pozitivna odprtina	Z
Minimalna hitrost aktiviranja	0,01 M/S
Oznaka kontaktne kode	B300, AC-15 (U _e = 240 V), I _e = 1,5 A EN/IEC 60947-5-1 dodatek A R300, DC-13 (U _e = 250 V), I _e = 0.1 A conforming to EN/IEC 60947-5-1 appendix A
[Ui] Nazivna izolacijska trdnost	300 VUL 508 500 V 3)IEC 60947-1 300 VCSA C22.2 št. 14

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

[Uimp] Nazivna napetostna trdnost ob impulzu	6 KV IEC 60664 6 KV IEC 60947-1
Kratkostična zaščita	10 A Modul Taliina varovalka gG
Električna vzdržljivost	5000000 Ciklov, DC-13 120 V, 4 W 60 cyc/mn 0,5 IEC 60947-5-1 dodatek C 5000000 Ciklov, DC-13 24 V, 10 W 60 cyc/mn 0,5 IEC 60947-5-1 dodatek C 5000000 Ciklov, DC-13 48 V, 7 W 60 cyc/mn 0,5 IEC 60947-5-1 dodatek C
Širina	31 Mm
Višina	65 Mm
Globina	30 Mm

Okolje

Združljivost izdelkov	XCKD
Temperatura okoliškega zraka za delovanje	-25...70 °C
Temperatura okoliškega zraka za skladiščenje	-40...70 °C

Packing Units

Teža embalaže 1	0,139 Kg
Višina embalaže 1	0,420 Dm
Širina embalaže 1	0,420 Dm
Dolžina embalaže 1	0,780 Dm

Offer Sustainability

Status trajnostne ponudbe	Izdelek Green Premium
Uredba REACH	 Izjava REACH
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS)  Izjava EU RoHS
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	 Da
Razkritje okoljskih podatkov	 Okoljski Profil Izdelka

Pogodbena garancija

Garancija	18 months
-----------	-----------