

ZCD29M12

Ohišje omejitvenega stikala ZCD - kompaktno -
2NC - hitro proženje - M12 5P



Glavno

Serija izdelka	Telemecanique Limit switches XC Standard
Ime serije	Standardni kompaktni
Izdelek ali sestavni del	Ohišje mejnega stikala
Kratko ime naprave	ZCD
Zasnova	Compact
Tip ohišja	Fiksen
Povezana glava	ZCE29 ZCE13 ZCE66 ZCE10 ZCE08 ZCE63 ZCE07 ZCEH0 ZCE24 ZCE09 ZCE02 ZCE21 ZCE06 ZCE27 ZCE65 ZCE01 ZCE64 ZCE28 ZCE11 ZCEH2 ZCE62 ZCE05 ZCE14 ZCE67
Material ohišja	Zamak
Število polov	2
Tip kontakta in sestava	2 NC
Premik kontakta	Hitro ukrepanje, simultano Hitro ukrepanje

Komplementarno

Električna povezava	Moški konektor M12, 5 zatičev
Kontaktna izolacijska oblika	ZB
Material kontaktov	Posrebreni kontakti
Pozitivna odprtina	Z
Minimalna hitrost aktiviranja	0,01 M/S
Oznaka kontaktne kode	B300, AC-15 (U _e = 240 V), I _e = 1,5 A EN/IEC 60947-5-1 dodatek A R300, DC-13 (U _e = 250 V), I _e = 0.1 A conforming to EN/IEC 60947-5-1 appendix A
[Ui] Nazivna izolacijska trdnost	300 VUL 508 500 V 3)IEC 60947-1 300 VCSA C22.2 št. 14
Maksimalna odpornost na terminalih	25 MOhm conforming to IEC 60255-7 category 3
[Uimp] Nazivna napetostna trdnost ob impulzu	6 KV IEC 60664 6 KV IEC 60947-1
Kratkostična zaščita	10 A Modul Taliilna varovalka gG

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

[Ie] nazivni obratovalni tok	3 A 50 V, AC-15 EN/IEC 60947-5-1 dodatek A 0,27 A 50 V, DC-13 EN/IEC 60947-5-1 dodatek A
[Ithe] običajni zaprt termični tok	4 A
Električna vzdržljivost	5000000 Ciklov, DC-13 24 V, 10 W 60 cyc/mn 0,5 IEC 60947-5-1 dodatek C 5000000 Ciklov, DC-13 48 V, 7 W 60 cyc/mn 0,5 IEC 60947-5-1 dodatek C
Širina	31 Mm
Višina	65 Mm
Globina	30 Mm

Okolje

Združljivost izdelkov	XCKD
Temperatura okoliškega zraka za delovanje	-25...70 °C
Temperatura okoliškega zraka za skladiščenje	-40...70 °C

Packing Units

Teža embalaže 1	0,163 Kg
Višina embalaže 1	0,340 Dm
Širina embalaže 1	0,330 Dm
Dolžina embalaže 1	1,000 Dm

Offer Sustainability

Status trajnostne ponudbe	Izdelek Green Premium
Uredba REACH	Izjava REACH
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) Izjava EU RoHS
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	Da
Razkritje okoljskih podatkov	Okoljski Profil Izdelka

Pogodbena garancija

Garancija	18 months
-----------	-----------