

# ZCD35

Ohišje omejitvenega stikala ZCD - kompaktno -  
1NC+2NO - počasna prekinitev



## Glavno

Serijska izdelka	Telemecanique Limit switches XC Standard
Ime serije	Standardni kompaktni
Izdelek ali sestavni del	Ohišje mejnega stikala
Kratko ime naprave	ZCD
Zasnova	Compact
Tip ohišja	Fiksen
Povezana glava	ZCE07 ZCE08 ZCE11 ZCE10 ZCE62 ZCE06 ZCE29 ZCE01 ZCEH2 ZCE02 ZCE05 ZCE67 ZCE13 ZCE66 ZCEH0 ZCE21 ZCE24 ZCE63 ZCE64 ZCE27 ZCE65 ZCE28 ZCE14
Material ohišja	Zamak
Število polov	3
Tip kontakta in sestava	1 NC + 2 NO
Premik kontakta	Slow-break, break before make

## Komplementarno

Povezana komponenta povezave	ZCDEP16 ZCDEG11 ZCDEN12 ZCDEG13 ZCDEF12 ZCDEP20
Električna povezava	Terminali z vijajčno objemko 1 x 0,34 do 2 x 0,75 mm <sup>2</sup>
Kontaktna izolacijska oblika	ZB
Material kontaktov	Posrebreni kontakti
Pozitivna odprtina	Z
Minimalna hitrost aktiviranja	6 M/S
Oznaka kontaktne kode	R300, DC-13 (U <sub>e</sub> = 250 V), I <sub>e</sub> = 0.1 A conforming to EN/IEC 60947-5-1 appendix A C300, AC-15 (U <sub>e</sub> = 240 V), I <sub>e</sub> = 0.75 A conforming to EN/IEC 60947-5-1 appendix A
[Ui] Nazivna izolacijska trdnost	300 VUL 508 300 VCSA C22.2 št. 14 400 V 3)IEC 60947-1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

[Uimp] Nazivna napetostna trdnost ob impulzu	4 KV IEC 60664 4 KV IEC 60947-1
Kratkostična zaščita	6 A Modul Talilna varovalka gG
Električna vzdržljivost	5000000 Ciklov, DC-13 120 V, 2 W 60 cyc/mn 0,5 IEC 60947-5-1 dodatek C 5000000 Ciklov, DC-13 24 V, 4 W 60 cyc/mn 0,5 IEC 60947-5-1 dodatek C 5000000 Ciklov, DC-13 48 V, 3 W 60 cyc/mn 0,5 IEC 60947-5-1 dodatek C
Širina	31 Mm
Višina	65 Mm
Globina	30 Mm

## Okolje

Združljivost izdelkov	XCKD
Temperatura okoliškega zraka za delovanje	-25...70 °C
Temperatura okoliškega zraka za skladiščenje	-40...70 °C

## Packing Units

Teža embalaže 1	0,142 Kg
Višina embalaže 1	0,800 Dm
Širina embalaže 1	0,430 Dm
Dolžina embalaže 1	0,430 Dm

## Offer Sustainability

Status trajnostne ponudbe	Izdelek Green Premium
Uredba REACH	 <a href="#">Izjava REACH</a>
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS)  <a href="#">Izjava EU RoHS</a>
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	 <a href="#">Da</a>
Razkritje okoljskih podatkov	 <a href="#">Okoljski Profil Izdelka</a>

## Pogodbena garancija

Garancija	18 months
-----------	-----------