

ZCD37

Ohišje omejitvenega stikala ZCD - kompaktno -
2NC+1NO - počasna prekinitev



Glavno

Serijska izdelka	Telemecanique Limit switches XC Standard
Ime serije	Standardni kompaktni
Izdelek ali sestavni del	Ohišje mejnega stikala
Kratko ime naprave	ZCD
Zasnova	Compact
Tip ohišja	Fiksen
Povezana glava	ZCE02 ZCEH2 ZCE62 ZCE10 ZCE08 ZCE66 ZCE65 ZCE27 ZCE28 ZCE01 ZCE05 ZCE11 ZCE64 ZCE14 ZCE07 ZCE67 ZCE13 ZCE63 ZCE29 ZCE21 ZCE06 ZCEH0 ZCE24
Material ohišja	Zamak
Število polov	3
Tip kontakta in sestava	2 NC + 1 NO
Premik kontakta	Slow-break, break before make

Komplementarno

Povezana komponenta povezave	ZCDEP16 ZCDEP20 ZCDEG11 ZCDEG13 ZCDEF12 ZCDEN12
Električna povezava	Terminali z vijajčno objemko 1 x 0,34 do 2 x 0,75 mm ²
Kontaktna izolacijska oblika	ZB
Material kontaktov	Posrebreni kontakti
Pozitivna odprtina	Z
Minimalna hitrost aktiviranja	6 M/S
Oznaka kontaktne kode	R300, DC-13 (U _e = 250 V), I _e = 0.1 A conforming to EN/IEC 60947-5-1 appendix A C300, AC-15 (U _e = 240 V), I _e = 0.75 A conforming to EN/IEC 60947-5-1 appendix A
[Ui] Nazivna izolacijska trdnost	300 VUL 508 300 VCSA C22.2 št. 14 400 V 3)IEC 60947-1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

[Uimp] Nazivna napetostna trdnost ob impulzu	4 KV IEC 60664 4 KV IEC 60947-1
Kratkostična zaščita	6 A Modul Talilna varovalka gG
Električna vzdržljivost	5000000 Cycles, DC-13 120 V, 1 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C 5000000 Ciklov, DC-13 24 V, 3 W 60 cyc/mn 0,5 IEC 60947-5-1 dodatek C 5000000 Ciklov, DC-13 48 V, 2 W 60 cyc/mn 0,5 IEC 60947-5-1 dodatek C
Širina	31 Mm
Višina	65 Mm
Globina	30 Mm

Okolje

Zdržljivost izdelkov	XCKD
Temperatura okoliškega zraka za delovanje	-25...70 °C
Temperatura okoliškega zraka za skladiščenje	-40...70 °C

Packing Units

Tip enote v embalaži 1	PCE
Število enot v embalaži 1	1
Teža embalaže 1	140 G
Višina embalaže 1	4,1 Cm
Širina embalaže 1	4,1 Cm
Dolžina embalaže 1	7,5 Cm
Tip enote v embalaži 2	S01
Število enot v embalaži 2	32
Teža embalaže 2	4,705 Kg
Višina embalaže 2	15 Cm
Širina embalaže 2	15 Cm
Dolžina embalaže 2	40 Cm

Offer Sustainability

Status trajnostne ponudbe	Izdelek Green Premium
Uredba REACH	 Izjava REACH
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS)  Izjava EU RoHS
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	 Da
Razkritje okoljskih podatkov	 Okoljski Profil Izdelka

Pogodbena garancija

Garancija	18 months
-----------	-----------