

ZCKD25

Glava omejitvenega stikala ZCKD -
termoplastični nastavljiv vzvod valjnega bata



Glavno

Serijski izdelki	Telemecanique Limit switches XC Standard
Ime serije	Standardni format
Izdelek ali sestavni del	Glava mejnega stikala
Kratko ime naprave	ZCKD
Tip glave	Glava bata
Združljivost izdelkov	XCKL XCKM
Povezano ohišje	ZCKLD39 ZCKMD35H7 ZCKM1H29 ZCKL7H7 ZCKM6H29 ZCKL6H7 ZCKMD31H29 ZCKM6 ZCKMD37H29 ZCKLD39H7 ZCKM5H29 ZCKM8H7 ZCKMD39 ZCKLD31H7 ZCKM1 ZCKMD37H7 ZCKM9 ZCKLD37H7 ZCKM5 ZCKM8H29 ZCKMD35H29 ZCKL1H7 ZCKL7 ZCKL8 ZCKM1H7 ZCKM8 ZCKMD39H29 ZCKMD31 ZCKLD35 ZCKM7 ZCKMD35 ZCKLD35H7 ZCKMD31H7 ZCKL1 ZCKMD39H7 ZCKM5H7 ZCKLD37 ZCKM9H29 ZCKM6H7 ZCKMD37 ZCKL6 ZCKL8H7 ZCKM7H7 ZCKL5H7 ZCKLD31 ZCKL5 ZCKM7H29
Gibanje operativne glave	Vrtljiv Linearno
Tip upravljanja	Valjni vzvod bata Povratna vzmet Termoplastično Nastavljiv
Tip pristopa	Bočni pristop, 1 smer

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Komplementarno

Stikalno aktiviranje	S 30° odmikom
Pozitivna odprtina	Z
Material glave	Plastika



Okolje

Temperatura okoliškega zraka za delovanje	-25...70 °C
Temperatura okoliškega zraka za skladiščenje	-40...70 °C
Okoljske značilnosti	Standard

Packing Units

Tip enote v embalaži 1	PCE
Število enot v embalaži 1	1
Teža embalaže 1	105 G
Višina embalaže 1	3,3 Cm
Širina embalaže 1	6 Cm
Dolžina embalaže 1	7,5 Cm

Offer Sustainability

Uredba REACH	 Izjava REACH
Direktiva EU ROHS	Se ne uporablja, zunaj področja uporabe direktive RoHS
Razkritje okoljskih podatkov	 Okoljski Profil Izdelka

Pogodbena garancija

Garancija	18 months
-----------	-----------