

Product data sheet

Characteristics

ZCKD26

Glava omejitvenega stikala ZCKD - jekleni nastavljivi vzvod valjnega bata



Glavno

Serija izdelka	Telemecanique Limit switches XC Standard
Ime serije	Standardni format
Izdelek ali sestavni del	Glava mejnega stikala
Kratko ime naprave	ZCKD
Tip glave	Glava bata
Združljivost izdelkov	XCKL XCKM
Povezano ohišje	ZCKLD37 ZCKMD31H29 ZCKL6H7 ZCKM7H29 ZCKL6 ZCKM8H29 ZCKM7H7 ZCKMD37 ZCKL7H7 ZCKM6 ZCKMD37H29 ZCKLD39H7 ZCKM9 ZCKMD39H29 ZCKLD35 ZCKLD31H7 ZCKL5H7 ZCKMD35 ZCKM6H7 ZCKMD37H7 ZCKL1 ZCKMD31 ZCKLD37H7 ZCKMD31H7 ZCKM6H29 ZCKM5H29 ZCKM1H7 ZCKM9H29 ZCKM8 ZCKL8 ZCKL5 ZCKM7 ZCKLD31 ZCKM8H7 ZCKL7 ZCKL8H7 ZCKMD35H29 ZCKM1 ZCKMD35H7 ZCKL1H7 ZCKLD39 ZCKMD39 ZCKM5 ZCKMD39H7 ZCKM1H29 ZCKM5H7 ZCKLD35H7
Gibanje operativne glave	Vrtljiv Linearno
Tip upravljanja	Valjni vzvod bata Povratna vzmet Kovinski Nastavljiv)
Tip pristopa	Bočni pristop, 1 smer

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Komplementarno

Stikalno aktiviranje	S 30° odmikom
Pozitivna odprtina	Z
Material glave	Plastika



Okolje

Temperatura okoliškega zraka za delovanje	-25...70 °C
Temperatura okoliškega zraka za skladiščenje	-40...70 °C
Okoljske značilnosti	Standard

Packing Units

Tip enote v embalaži 1	PCE
Število enot v embalaži 1	1
Teža embalaže 1	117 G
Višina embalaže 1	3,3 Cm
Širina embalaže 1	6 Cm
Dolžina embalaže 1	7,5 Cm

Offer Sustainability

Uredba REACH	 Izjava REACH
Direktiva EU ROHS	Se ne uporablja, zunaj področja uporabe direktive RoHS
Razkritje okoljskih podatkov	 Okoljski Profil Izdelka

Pogodbena garancija

Garancija	18 months
-----------	-----------