

ZCKE066

Glava omejitvenega stikala ZCKE - mačji brk -
-40 °C



Glavno

Serijska izdelka	Telemecanique Limit switches XC Standard
Ime serije	Standardni format
Izdelek ali sestavni del	Glava mejnega stikala
Kratko ime naprave	ZCKE
Tip glave	Večsmerna glava
Združljivost izdelkov	XCKJ
Povezano ohišje	ZCKJ2H7 ZCKJ1 ZCKJD31H7 ZCKJ8H29 ZCKJD35 ZCKJ21H29 ZCKJD39H29 ZCKJ7H29 ZCKJD37H7 ZCKJD37H29 ZCKJ11H29 ZCKJ9 ZCKJ1H7 ZCKJ6 ZCKJ1H29 ZCKJ5 ZCKJ8 ZCKJ7 ZCKJ2 ZCKJ21H7 ZCKJD37 ZCKJD35H29 ZCKJ9H29 ZCKJ5H7 ZCKJ21 ZCKJ6H7 ZCKJ7H7 ZCKJ2H29 ZCKJD31 ZCKJD35H7 ZCKJ8H7 ZCKJD39 ZCKJ11H7 ZCKJ11 ZCKJD31H29 ZCKJ9H7 ZCKJD39H7 ZCKJ5H29 ZCKJ6H29
Gibanje operativne glave	Večsmerno
Tip upravljanja	Mačji brk Povratna vzmet
Tip pristopa	Večstranski pristop

Komplementarno

Stikalno aktiviranje	S katerim koli gibljivim delom
Pozitivna odprtina	Brez
Teža izdelka	0,115 Kg
Material glave	Kovinski

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Okolje

Temperatura okoliškega zraka za delovanje	-40...70 °C
Temperatura okoliškega zraka za skladiščenje	-40...70 °C
Okoljske značilnosti	Nizka temperatura

Packing Units

Teža embalaže 1	0,115 Kg
Višina embalaže 1	1,600 Dm
Širina embalaže 1	0,360 Dm
Dolžina embalaže 1	0,360 Dm

Offer Sustainability

Status trajnostne ponudbe	Izdelek Green Premium
Uredba REACH	Izjava REACH
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) Izjava EU RoHS
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	Da
Razkritje okoljskih podatkov	Okoljski Profil Izdelka

Pogodbena garancija

Garancija	18 months
-----------	-----------