

Product data sheet

Characteristics

ZCKE08TK

Glava omejitvenega stikala ZCKE - vzmetna palica



Glavno

Serijski izdelki	Telemecanique Limit switches XC Standard
Ime serije	Standardni format
Izdelek ali sestavni del	Glava mejnega stikala
Kratko ime naprave	ZCKE
Tip glave	Večsmerna glava
Združljivost izdelkov	XCKJ
Povezano ohišje	ZCKJ7 ZCKJD35H29 ZCKJD31H29 ZCKJ21H7 ZCKJD37 ZCKJ11 ZCKJD31 ZCKJ21 ZCKJ7H29 ZCKJ8H7 ZCKJD37H7 ZCKJD31H7 ZCKJ8 ZCKJD39 ZCKJD35 ZCKJ11H7 ZCKJ2H29 ZCKJ1 ZCKJ21H29 ZCKJD35H7 ZCKJ5 ZCKJ7H7 ZCKJ2 ZCKJ2H7 ZCKJ6H7 ZCKJ1H7 ZCKJ9 ZCKJ6H29 ZCKJ1H29 ZCKJ9H29 ZCKJ5H29 ZCKJ8H29 ZCKJ9H7 ZCKJD39H7 ZCKJD39H29 ZCKJ11H29 ZCKJ6 ZCKJD37H29 ZCKJ5H7
Gibanje operativne glave	Večsmerno Vrtljiv
Tip upravljanja	Vzmetna palica Povratna vzmet
Tip pristopa	Večstranski pristop

Komplementarno

Stikalno aktiviranje	S katerim koli gibljivim delom
Pozitivna odprtina	Brez
Material glave	Kovinski

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Okolje

Temperatura okoliškega zraka za delovanje	-25...70 °C
Temperatura okoliškega zraka za skladičenje	-40...70 °C
Okoljske značilnosti	Korozivni

Packing Units

Tip enote v embalaži 1	PCE
Število enot v embalaži 1	1
Teža embalaže 1	132 G
Višina embalaže 1	3,7 Cm
Širina embalaže 1	3,7 Cm
Dolžina embalaže 1	16,2 Cm

Offer Sustainability

Uredba REACH	Izjava REACH
Direktiva EU ROHS	Se ne uporablja, zunaj področja uporabe direktive RoHS
Razkritje okoljskih podatkov	Okoljski Profil Izdelka

Pogodbena garancija

Garancija	18 months
-----------	-----------