

ZCKE215

Glava omejitvenega stikala ZCKE -
termoplastični vzvod valjnega bata - +120 °C



Glavno

Serijska izdelka	Telemecanique Limit switches XC Standard
Ime serije	Standardni format
Izdelek ali sestavni del	Glava mejnega stikala
Kratko ime naprave	ZCKE
Tip glave	Glava bata
Združljivost izdelkov	XCKJ
Povezano ohišje	ZCKJD37H29 ZCKJ11 ZCKJ5H7 ZCKJD39H29 ZCKJ2H7 ZCKJ5H29 ZCKJ1H7 ZCKJD39H7 ZCKJ11H29 ZCKJD35H7 ZCKJD31H7 ZCKJ7H29 ZCKJ8H29 ZCKJD31H29 ZCKJ2 ZCKJ1 ZCKJD35 ZCKJ5 ZCKJ6 ZCKJ21H7 ZCKJ41 ZCKJD37 ZCKJ9 ZCKJ11H7 ZCKJ7H7 ZCKJ21H29 ZCKJ41H29 ZCKJ4 ZCKJ2H29 ZCKJD37H7 ZCKJ4H29 ZCKJD35H29 ZCKJD39 ZCKJ9H29 ZCKJ6H7 ZCKJ21 ZCKJ9H7 ZCKJD31 ZCKJ8H7 ZCKJ6H29 ZCKJ41H7 ZCKJ7 ZCKJ1H29 ZCKJ8 ZCKJ4H7
Gibanje operativne glave	Linearno
Tip upravljanja	Valjni vzvod bata Povratna vzmet Termoplastično
Tip pristopa	Bočni pristop, 1 smer

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Komplementarno

Stikalno aktiviranje	S 30° odmikom
Pozitivna odprtina	Z
Teža izdelka	0,185 Kg
Material glave	Kovinski

Okolje

Temperatura okoliškega zraka za delovanje	10...120 °C
Temperatura okoliškega zraka za skladiščenje	10...120 °C
Okoljske značilnosti	Visoka temperatura

Packing Units

Teža embalaže 1	0,185 Kg
Višina embalaže 1	0,060 Dm
Širina embalaže 1	0,044 Dm
Dolžina embalaže 1	0,055 Dm

Offer Sustainability

Status trajnostne ponudbe	Izdelek Green Premium
Uredba REACH	Izjava REACH
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) Izjava EU RoHS
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	Da
Razkritje okoljskih podatkov	Okoljski Profil Izdelka

Pogodbena garancija

Garancija	18 months
-----------	-----------