

## ZCKE61

Glava omejitvenega stikala ZCKE - bat s kovinskim zaključkom



### Glavno

Serijski izdelki	Telemecanique Limit switches XC Standard
Ime serije	Standardni format
Izdelek ali sestavni del	Glava mejnega stikala
Kratko ime naprave	ZCKE
Tip glave	Glava bata
Združljivost izdelkov	XCKJ
Povezano ohišje	ZCKJ8 ZCKJ9H29 ZCKJ6H29 ZCKJ41H29 ZCKJD37 ZCKJD39H7 ZCKJ2H7 ZCKJD35H7 ZCKJ41 ZCKJ7H7 ZCKJD35 ZCKJ11H7 ZCKJ1H7 ZCKJ1H29 ZCKJ5H7 ZCKJ5H29 ZCKJ7 ZCKJD31 ZCKJ41H7 ZCKJ5 ZCKJ4H29 ZCKJ6H7 ZCKJD35H29 ZCKJD37H7 ZCKJ8H7 ZCKJ7H29 ZCKJD39H29 ZCKJ4 ZCKJ21H7 ZCKJ11 ZCKJ21H29 ZCKJ6 ZCKJ9H7 ZCKJ2H29 ZCKJ9 ZCKJ4H7 ZCKJD31H29 ZCKJD31H7 ZCKJ2 ZCKJ11H29 ZCKJD37H29 ZCKJ8H29 ZCKJD39 ZCKJ21 ZCKJ1
Gibanje operativne glave	Linearno
Tip upravljanja	Zaključni bat Povratna vzmet Kovinski
Tip pristopa	Vertikalni pristop, 1 smer

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Komplementarno

Stikalno aktiviranje	Na koncu
Pozitivna odprtina	Z
Material glave	Kovinski

## Okolje

Temperatura okoliškega zraka za delovanje	-25...70 °C
Temperatura okoliškega zraka za skladiščenje	-40...70 °C
Okoljske značilnosti	Standard

## Packing Units

Teža embalaže 1	0,142 Kg
Višina embalaže 1	0,400 Dm
Širina embalaže 1	0,480 Dm
Dolžina embalaže 1	0,900 Dm

## Offer Sustainability

Status trajnostne ponudbe	Izdelek Green Premium
Uredba REACH	<a href="#">Izjava REACH</a>
Direktiva EU ROHS	Proaktivno zagotavljanje skladnosti (izdelek je zunaj področja uporabe direktive EU RoHS) <a href="#">Izjava EU RoHS</a>
Brez živega srebra	Da
Informacije o izvzetju iz RoHS	<a href="#">Da</a>
Razkritje okoljskih podatkov	<a href="#">Okoljski Profil Izdelka</a>

## Pogodbena garancija

Garancija	18 months
-----------	-----------